

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: ADOCURE SEALER PF

Use / description of product: Solvent borne curing and sealing agent for concrete

Company name: Adomast Building Chemicals Ltd

Unit G

Lea Road Trading Estate

Waltham Abbey

Essex

EN9 1AE

Tel: 01992 710684

Fax: 01992 712813

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: KEROSENE (PETROLEUM) 30-50%

EINECS: 232-366-4 CAS: 8008-20-6

[Xi] R38; [N] R51/53; [Xn] R65; [-] R10

- XYLENE 1-10%

EINECS: 215-535-7 CAS: 1330-20-7

[-] R10; [Xn] R20/21; [Xi] R38

- CUMENE <1%

EINECS: 202-704-5 CAS: 98-82-8

[-] R10; [Xi] R37; [N] R51/53; [Xn] R65

- MESITYLENE 1-10%

EINECS: 203-604-4 CAS: 108-67-8

[-] R10; [Xi] R37; [N] R51/53

- 1,2,4-TRIMETHYLBENZENE 1-10%

EINECS: 202-436-9 CAS: 95-63-6

[-] R10; [Xn] R20; [Xi] R36/37/38; [N] R51/53

- STRAIGHT RUN Kerosine - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH.

30-50%

EINECS: 265-191-7 CAS: 64742-88-7

[Xn] R65; [Xi] R38; [N] R51/53

3. HAZARDS IDENTIFICATION

Main hazards: Flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: KEROSENE (PETROLEUM)

WEL (8 hr exposure limit): 5 mg/m³

- XYLENE

WEL (8 hr exposure limit): 220 mg/m³ WEL (15 min exposure limit): 441 mg/m³

- CUMENE

WEL (8 hr exposure limit): 125 mg/m³ WEL (15 min exposure limit): 250 mg/m³

- MESITYLENE

WEL (8 hr exposure limit): 25 ppm

- 1,2,4-TRIMETHYLBENZENE

WEL (8 hr exposure limit): 100 mg/m³ WEL (15 min exposure limit): 200 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Viscosity: Non-viscous

Flammability limits %: lower: 0.6

upper: 8

Flash point°C: 38

Relative density: .815

VOC g/l: 750

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: XYLENE

ORL MUS LD50 2119 mg/kg

ORL RAT LD50 4300 mg/kg

SCU RAT LD50 1700 mg/kg

- CUMENE

ORL MUS LD50 12750 mg/kg

ORL RAT LD50 1400 mg/kg

- MESITYLENE

IPR GPG LDLO 1303 mg/kg

- 1,2,4-TRIMETHYLBENZENE

IPR RAT LDLO 1752 mg/kg

ORL RAT LD50 5 gm/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

- Persistence and degradability:** Biodegradable.
- Bioaccumulative potential:** No bioaccumulation potential.
- Other adverse effects:** Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

- Disposal operations:** Dispose of via an authorised person / licensed waste disposal contractor in accordance with local regulations.
See accidental release measures
- Waste code number:** 16 03 03*
- Disposal of packaging:** Any special regulatory disposal status or provisions applicable to the product may also apply to empty containers or packaging if they contain, or are impaired with residual material -
- NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

- UN no:** 1993 **ADR Class:** 3
- Packing group:** II **Classification code:** F1
- Shipping name:** FLAMMABLE LIQUID, N.O.S.
- Labelling:** 3 **Hazard ID no:** 33



IMDG / IMO

- UN no:** 1993 **Class:** 3
- Packing group:** II **EmS:** F-E,S-E*
- Marine pollutant:** . **Labelling:** 3

IATA / ICAO

- UN no:** 1993 **Class:** 3
- Packing group:** II **Packing instructions:** 305(P&CA); 307(CAO)
- Labelling:** 3

15. REGULATORY INFORMATION

- Hazard symbols:** Dangerous for the environment.
Harmful.



- Risk phrases:** R10: Flammable.
R38: Irritating to skin.

SAFETY DATA SHEET

ADOCURE SEALER PF

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

Safety phrases: S61: Avoid release to the environment. Refer to special instructions / safety data sheets.
S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin.

R37: Irritating to respiratory system.

R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.