

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 09.10.2007

Revision: 09.10.2007

1 Identification of substance

- **Product details**
- **Trade name** Graffiti Protector PUR, Base
- **Article number:** 9930
- **Application of the substance / the preparation** Sealing
- **Manufacturer/Supplier:**
Remmers Baustofftechnik GmbH
Postfach 1255
D-49624 Lönningen / Germany
Tel.: 05432/83-0
Fax: 05432/3985
- **Informing department:**
Product Safety department: Tel.: +49 (0)5432/83-138/-538
E-Mail: sales@remmers.co.uk
- **Emergency information:**
during working hours:
U.K.: Tel.: +44 (0) 845 373 0103
Far East: Tel.: +65(0) 67410277
Head Office Germany: Tel.: +49 (0)5432 83 185
after working hours: Tel.: +49 (0)171/6428-297

2 Hazards identification

- **Hazard designation:**



Xn Harmful
N Dangerous for the environment

- **Information pertaining to particular dangers for man and environment**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 10 Flammable.

R 20/21 Harmful by inhalation and in contact with skin.

R 36/37/38 Irritating to eyes, respiratory system and skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- **Classification system**

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

3 Composition/information on ingredients

- **Chemical characterization**

- **Description:** Mixture of the substances listed below with harmless additions.

- **Dangerous components:**

CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate Xi; R 10-36	10-30%
	Solvent naphtha (mineral oil), slight aromatic Xn, Xi, N; R 10-37-51/53-65-66-67	10-30%

(Contd. on page 2)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 09.10.2007

Revision: 09.10.2007

Trade name **Graffiti Protector PUR, Base**

(Contd. of page 1)

CAS: 1330-20-7 EINECS: 215-535-7	xylene, mixed isomers, pure Xn, Xi; R 10-20/21-38	10-30%
CAS: 95-63-6 EINECS: 202-436-9	1,2,4-trimethylbenzene Xn, Xi, N; R 10-20-36/37/38-51/53	5-<10%
CAS: 108-67-8 EINECS: 203-604-4	mesitylene Xi, N; R 10-37-51/53	1-5%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene Xn, F; R 11-20	1-5%
CAS: 98-82-8 EINECS: 202-704-5	isopropylbenzene Xn, Xi, N; R 10-37-51/53-65	1-5%
CAS: 111-76-2 EINECS: 203-905-0	2-butoxyethanol Xn, Xi; R 20/21/22-36/38	<1.0%

· **Additional information** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· General information

If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally.

· After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Remove contaminated clothing.

Wash off immediately with water.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

· After swallowing

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

5 Fire fighting measures

· Suitable extinguishing agents

CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· For safety reasons unsuitable extinguishing agents

Water with a full water jet.

· Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained breathing apparatus.

· Additional information

Collect contaminated fire fighting water separately. It must not enter drains.

6 Accidental release measures

· Person-related safety precautions:

Wear protective equipment. Keep unprotected persons away.

· Measures for environmental protection:

Dilute with plenty of water.

· Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

GB

(Contd. on page 3)

Trade name **Graffiti Protector PUR, Base**

(Contd. of page 2)

7 Handling and storage

- **Handling**
- **Information for safe handling:** Ensure good ventilation/exhaust in workplaces.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information on storage in a common storage facility:** none
- **Further information about storage conditions:** Keep container tightly closed.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Components with limit values that require monitoring at the workplace:**

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
	Sk

1330-20-7 xylene, mixed isomers, pure

WEL	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV

95-63-6 1,2,4-trimethylbenzene

WEL	Long-term value: 125 mg/m ³ , 25 ppm
	ILV

108-67-8 mesitylene

WEL	Long-term value: 125 mg/m ³ , 25 ppm
	ILV

100-41-4 ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm
	Long-term value: 441 mg/m ³ , 100 ppm

98-82-8 isopropylbenzene

WEL	Short-term value: 250 mg/m ³ , 50 ppm
	Long-term value: 125 mg/m ³ , 25 ppm
	Sk

- **Additional information:** The lists that were valid during compilation were used as a basis.
- **Personal protective equipment**
- **General protective and hygienic measures**
Keep away from food, beverages and animal feed.
Immediately remove soiled, saturated clothing.
Wash hands before pauses and after work.
Avoid contact with eyes and skin.
- **Respiratory equipment:**
Filter A (brown)
In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.
- **Protection of hands:** Solvent resistant gloves
- **Material of gloves**
Nitrile rubber, NBR
Natural rubber, NR
Neoprene gloves

(Contd. on page 4)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 09.10.2007

Revision: 09.10.2007

Trade name **Graffiti Protector PUR, Base**

(Contd. of page 3)

- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Tightly sealed safety glasses.
- **Body protection:** Closed work clothing

9 Physical and chemical properties:

· General Information

Form:	Fluid
Colour:	According to product specification
Odour:	Like aromatic solvents

· Change in condition

Melting point/Melting range:	Not determined
Boiling point/Boiling range:	Not determined

· **Flash point:** 23°C

· **Self-inflammability:** Product is not self-igniting.

· **Danger of explosion:** Product is not explosive. However, formation of dangerous explosive vapour/air mixtures is possible.

· Explosive Limits:

Lower:	0.8 Vol %
Upper:	12 Vol %

· **Vapour pressure at 20°C:** 5 hPa

· **Density at 20°C** 1 g/cm³

· Solubility in / Miscibility with

Water: Slightly soluble

· Solvent content:

Organic solvents: 65 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known
- **Dangerous decomposition products:**
Carbon monoxide and carbon dioxide
as well as other toxic gases and vapours.

11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:**
Irritates skin and mucous membranes.
Dries skin out.
- **on the eye:** Irritating effect.
- **Sensitisation:** No sensitising effect known.
- **Additional toxicological information:**
The product shows the following dangers based on the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:
Harmful

(Contd. on page 5)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 09.10.2007

Revision: 09.10.2007

Trade name **Graffiti Protector PUR, Base**

Irritant

(Contd. of page 4)

12 Ecological information:

- **General notes:**

Water hazard class 2 : hazardous to water.

Do not allow product to reach ground water, bodies of water or sewage system.

13 Notes on disposal:

- **Product:**

- **Recommendation**

Do not dispose of together with household garbage. Do not allow product to reach sewage system.

Must be specially treated in compliance with official regulations.

- **Uncleaned packaging:**

- **Recommendation:**

Only completely empty containers may be recycled.

Disposal must be made according to official regulations.

- **Recommended cleaning agent:** Water, if necessary with cleaning agent.

14 Transport information

- **Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)**



- **ADR/RID-GGVS/E Class:** 3 (F1) Flammable liquids.

- **Kemler Number:** 30

- **UN-Number:** 1263

- **Packaging group:** III

- **Danger sign:** 3

- **Designation of goods:** 1263 PAINT

- **Limited quantities (LQ)** LQ7

- **Tunnel restriction code** E

- **Maritime transport IMDG/GGVSea:**



- **IMDG/GGVSea Class:** 3

- **UN Number:** 1263

- **Label** 3

- **Packaging group:** III

- **EMS Number:** F-E,S-E

- **Marine pollutant:** No

- **Correct technical name:** PAINT

(Contd. on page 6)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 09.10.2007

Revision: 09.10.2007

Trade name **Graffiti Protector PUR, Base**

(Contd. of page 5)

· **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1263
- **Label** 3
- **Packaging group:** III
- **Correct technical name:** PAINT

15 Regulatory information

· **Designation according to EC guidelines:**

The product has been classified and labelled in accordance with EC Guidelines / Ordinance on Hazardous Materials (GefStoffV)

· **Code letter and hazard designation of product:**



Xn Harmful
N Dangerous for the environment

· **Hazard-determining components of labelling:**

Solvent naphtha (mineral oil), slight aromatic xylene, mixed isomers, pure

· **Risk phrases:**

- 10 Flammable.
- 20/21 Harmful by inhalation and in contact with skin.
- 36/37/38 Irritating to eyes, respiratory system and skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Safety phrases:**

- 24/25 Avoid contact with skin and eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 36/37 Wear suitable protective clothing and gloves.
- 51 Use only in well-ventilated areas.
- 57 Use appropriate container to avoid environmental contamination.
- 60 This material and its container must be disposed of as hazardous waste.

· **National regulations**

· **Technical instructions (air):**

Class	Proportion in %
NK	60-<80

- **Water hazard class:** Water hazard class 2: hazardous to water.

16 Other information:

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

· **Relevant R-phrases**

- 10 Flammable.
- 11 Highly flammable.
- 20 Harmful by inhalation.
- 20/21 Harmful by inhalation and in contact with skin.
- 20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
- 36 Irritating to eyes.
- 36/37/38 Irritating to eyes, respiratory system and skin.
- 36/38 Irritating to eyes and skin.
- 37 Irritating to respiratory system.

(Contd. on page 7)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 09.10.2007

Revision: 09.10.2007

Trade name Graffiti Protector PUR, Base

(Contd. of page 6)

- 38 Irritating to skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· **Department issuing data specification sheet:** Product Safety department

GB