

Data Sheet

ADOCOAT

ALUMINIUM PAINT



Description

A bright aluminium traditional, solar reflective coating suitable for application to bituminous roofing substrates.

Uses

For the protection against sun and weathering of roofs, particularly where bituminous, exposed steel and corrugated iron surfaces are encountered.

Coverage

1.1 to 1.7 m² per litre per coat of undiluted material.

Typical properties

Colour	Aluminium
Specific Gravity	1.0 @ 20°C
Flash Point	38 °C
Water Resistance	Resistant to water and most salt solutions
Acids and Alkalis	Not resistant
Solvents	Not resistant

Use

Preparation and Application Requirements

ADOCOAT ALUMINIUM PAINT should always be applied to surfaces that are clean and free from dust, oil and other surface contaminants. Freshly applied bitumen coating should be allowed to weather for 2-3 weeks before application of **ADOCOAT ALUMINIUM PAINT**. It should not be applied in temperatures below 5° C and the applied material should be protected from frost or rain until it has completely dried. Drying time is 3 to 6 hours but this may be extended in humid or poorly ventilated situations.

Stir well before use.

Apply by brush or spray. To avoid staining it is important that **ADOCOAT ALUMINIUM PAINT** is not applied too thickly. Do not brush excessively as this can cause softening of the substrate.

Coverage

Approximately 10m² per coat, depending upon the texture and porosity of the surface.

Cleaning

Tools should be cleaned immediately after use with **ADOWASH**.

Storage

ADOCOAT ALUMINIUM PAINT should be stored in a closed container in a cool, dry area and protected from sources of ignition. In good conditions, storage life should exceed 12 months.

Specification Clause

ADOCOAT ALUMINIUM PAINT supplied by **ADOMAST** Building Chemicals Limited should be applied according to manufacturer's instructions.

Data Sheet

ADOCOAT

ALUMINIUM PAINT



Health and Safety

Care should be taken to avoid splashes entering eyes. Contact with skin should be avoided and hands washed thoroughly in the event of accidental contact. **ADOCOAT ALUMINIUM PAINT** should not be ingested. If splashes affect eyes, they should be bathed immediately with copious quantities of clean water and if discomfort persists medical attention should be sought without delay. Please refer to separate Health & Safety data sheet.