

Data Sheet

ADOFLOOR EPOXY

Epoxy Resin Based Primer



Description

ADOFLOOR EPOXY is a two pack system ideal for surface sealing and bonding of **ADOFLOOR** toppings where it will also improve resistance to damp penetration. Its extended open time makes it especially suitable for bonding **ADOFLOOR** floor toppings.

Appearance

Mixed material forms an emulsion with an off-white milky colour that disappears after application to leave a clear transparent film.

Use

Surface Preparation

Surfaces should be sound, clean, free from laitance, dust, oils or other deposits. The prepared surface should be free from surface water but residual dampness can be tolerated.

Mixing

Entire contents of Base and Hardener containers should be thoroughly mixed in clean plastic bucket or similar to obtain a completely uniform blend, then using empty Base container as a measure, mix in one full measure of clean water.

Application

Immediately after mixing, brush the adhesive on to the prepared surface, brushing in two directions at right angles to each other. Apply the **ADOFLOOR** topping whilst adhesive is still tacky. Tackiness may still be evident after 8 hours dependent upon ambient temperature but as a general guide topping should be applied within 4 hours. On extremely porous surfaces or where first coat is no longer tacky, apply an additional coat.

Do not apply in temperatures below 5°C.

Coverage

A 3.3 Kg pack will cover up to 20 m² when diluted and up to 15 m² when used neat.

An 8.25 Kg pack will cover up to 50 m² when diluted and up to 38 m² when used neat, dependent upon surface texture and porosity.

Pot Life

This is influenced by temperature, volume of mixed material and quantity of added water. In practice under normal conditions a pot life of approximately 60 minutes can be expected.

Cure Time

Full cure is achieved after approximately 7 days at 20⁰ C. Lower temperatures will prolong cure time.

Cleaning of Equipment

Brushes and equipment should be washed thoroughly in clean water immediately after use and before material begins to set.

Storage

Lea Road, Trading Estate, Waltham Abbey, Essex EN9 1AE
Tel: 01992 710 684 Fax: 01992 712 813
Email: sales@adomast.co.uk Website: <http://www.adomast.co.uk>

ABCD 591 Issue: 1
Issued: Mar 2001

Data Sheet
ADOFLOOR EPOXY
Epoxy Resin Based Primer



Keep all containers sealed, store at room temperature and away from direct heat. Under normal temperate and dry conditions storage life is in excess of one year.

Health & Safety

ADOFLOOR EPOXY should be handled carefully and skin contact, exposure to high vapour concentrations and ingestion avoided. Wearing of overalls, gloves and protective eyewear should be considered together with the application of a suitable barrier cream to hands where necessary.

Reference should be made to the separate **ADOFLOOR EPOXY** Health and Safety literature.