

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** ADOLEASE  
**Company name:** Adomast Building Chemicals Ltd  
Unit G  
Lea Road Trading Estate  
Waltham Abbey  
Essex  
EN9 1AE  
Tel: 01992 710684  
Fax: 01992 712813

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** KEROSENE (PETROLEUM) 70-90%  
EINECS: 232-366-4 CAS: 8008-20-6  
[Xi] R38; [N] R51/53; [Xn] R65; [-] R10

- PETROLEUM DISTILLATE 1-10%  
EINECS: 265-149-8 CAS: 64742-47-8  
[Xn] R65; [Xi] R66

### 3. HAZARDS IDENTIFICATION

**Main hazards:** Flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be irritation and redness at the site of contact.  
**Eye contact:** There may be irritation and redness. The eyes may water profusely.  
**Ingestion:** There may be soreness and redness of the mouth and throat.  
**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

### 4. FIRST AID MEASURES (ACTION)

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.  
**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.  
**Ingestion:** Wash out mouth with water. Consult a doctor.  
**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 5. FIRE-FIGHTING MEASURES

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.  
**Exposure hazards:** In combustion emits toxic fumes.  
**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**7. HANDLING AND STORAGE**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Hazardous ingredients:** KEROSENE (PETROLEUM)  
WEL (8 hr exposure limit): 5 mg/m<sup>3</sup>

- PETROLEUM DISTILLATE  
WEL (8 hr exposure limit): 5 mg/m<sup>3</sup>

**Engineering measures:** Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**State:** Liquid

**Colour:** Yellow-brown

**Odour:** Characteristic odour

**Solubility in water:** Not miscible

**Also soluble in:** Petroleum ether.

**Viscosity:** Non-viscous

**Viscosity value:** 7

**Viscosity test method:** Kinematic viscosity in 10<sup>-6</sup> m<sup>2</sup>/s at 40°C (ISO 3104/3105)

**Flash point°C:** 38

**Relative density:** .81

**10. STABILITY AND REACTIVITY**

**Stability:** Stable under normal conditions.

**Conditions to avoid:** Heat.

**Materials to avoid:** Strong oxidising agents. Strong acids.

**Haz. decomp. products:** In combustion emits toxic fumes.

### 11. TOXICOLOGICAL INFORMATION

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

### 12. ECOLOGICAL INFORMATION

**Mobility:** Readily absorbed into soil.

**Persistence and degradability:** Not biodegradable.

**Bioaccumulative potential:** Bioaccumulation potential.

**Other adverse effects:** Toxic to aquatic organisms. Toxic to soil organisms.

### 13. DISPOSAL CONSIDERATIONS

**Disposal operations:** Dispose of via an authorised person / licensed waste disposal contractor in accordance with local regulations.

See accidental release measures

**Waste code number:** 16 03 03\*

**Disposal of packaging:** Any special regulatory disposal status or provisions applicable to the product may also apply to empty containers or packaging if they contain, or are impaired with residual material -

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

### 14. TRANSPORT INFORMATION

#### ADR / RID

**UN no:** 1993

**ADR Class:** 3

**Packing group:** III

**Classification code:** F1

**Shipping name:** FLAMMABLE LIQUID, N.O.S.

**Labelling:** 3

**Hazard ID no:** 30



#### IMDG / IMO

**UN no:** 1993

**Class:** 3

**Packing group:** III

**EmS:** F-E,S-E\*

**Marine pollutant:** .

**Labelling:** 3

#### IATA / ICAO

**UN no:** 1993

**Class:** 3

**Packing group:** III

**Packing instructions:** 309(P&CA); 310(CAO)

**Labelling:** 3

### 15. REGULATORY INFORMATION

**Hazard symbols:** Irritant.

Dangerous for the environment.



**Risk phrases:** R10: Flammable.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases:** S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

## 16. OTHER INFORMATION

**Risk phrases used in s.2:** R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R10: Flammable.

R66: Repeated exposure may cause skin dryness or cracking.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.