

SAFETY DATA SHEET

RESOMAST PIN GROUT SF CARTRIDGE

1.00 IDENTIFICATION OF COMPOUND **RESOMAST PIN GROUT SF CARTRIDGE:** Two part product containing a styrene free polyester resin and a hardener

1.10 IDENTIFICATION OF MANUFACTURER

Adomast Building Chemicals Ltd.
Unit G, Lea Road Trading Estate, Waltham Abbey, Essex EN9 1AE
Telephone: 01992 710 684 Fax: 01992 712 813

2.00 COMPOSITION/INFORMATION ON INGREDIENTS

Resin Component Contains:

Chemical name	CAS No	Concentration(%w/w)	Hazard
Symbol			
Methacrylate Monomers	100-42-5	< 20%	

Hardener Component Contains:

Chemical name	CAS No	Concentration(%w/w)	Hazard
Symbol			
Dibenzoyl peroxide	94-36-0	< 18%	Xi

3.00 HAZARDS IDENTIFICATION

Resin component – Irritant vapour. Irritating to eyes and skin.
Hardener component - May cause fire. May cause sensitisation by skin contact. May be irritating to the eyes.

4.00 FIRST AID MEASURES

Eyes: Flush eyes with copious amounts of water. Seek medical advice.
Skin: Remove contaminated clothing, taking care not to contaminate unaffected areas. Wash skin with soap and water. Seek medical advice if symptoms persist. **Inhalation:** If inhalation of high concentrations of vapour or dust should occur, remove victim from exposure. Obtain medical attention.
Ingestion: Do not induce vomiting. Wash out mouth with water, give 200-300 ml of water to drink and seek medical attention.

5.00 FIRE FIGHTING MEASURES

Extinguishing Media: Dry powder, foam, water fog. **Unsuitable Extinguishing Media:** Water jets, halones. **Special protective equipment:** Wear suitable clothing to prevent eye/skin contact occurring. Wear suitable breathing apparatus.

6.00 ACCIDENTAL RELEASE MEASURES

Environmental Precautions: Do not allow product to enter drains or water courses. Advise local authorities if this is not possible. **Clean Up Methods:** Scrape up and place in suitable container for disposal.

7.00 HANDLING AND STORAGE

Handling: Avoid contact with eyes/skin. Do not breathe vapour. Provide adequate ventilation, including local extraction if necessary. Keep products and emptied containers away from heat and sources of ignition. **Storage:** Store in a dry, well ventilated area. Protect containers from heat. Keep containers closed and dry when not in use. Do not store near food and drink.

8.00 EXPOSURE CONTROLS/PERSONAL PROTECTION

Resin component -
Avoid inhaling fumes. Use in well ventilated space. Wear gloves at all times.
Hardener component contains: Dibenzoyl peroxide LTEL: 5mg/m³ 8hr TWA
Gloves should be used. Wear suitable breathing apparatus in confined or poorly ventilated spaces if local exhaust ventilation is not possible.

9.00 PHYSICAL AND CHEMICAL PROPERTIES

Resin component:

Form: Thick coloured paste **Odour:** Ester like
Flash Point (°C): > 100 **Specific gravity:** 1.65
Flammability: Not established

Hardener component:

Form: White smooth paste **Odour:** Faint
Flash Point (°C): Above the SADT **Specific gravity:** 1.60
Flammability: Will support combustion if involved in fire

10.00 STABILITY AND REACTIVITY

Conditions to avoid: Do not leave containers open when not in use. Protect from high temperatures. **Hardener component** – A dangerous self accelerating decomposition reaction and under certain circumstances explosion or fire can be caused by direct contact with incompatible substances

or by thermal decomposition. **Materials to avoid:** **Resin component** - Oxidising agents and peroxides. **Hardener component** - Acids, alkalis, heavy metals, reducing agents, rust. **Hazardous decomposition products:** Acrid smoke and irritating fumes upon thermal decomposition of the product including : **Resin** - Oxides of carbon and smoke. **Hardener** - Benzoic acid, benzene and phenyl benzoate

11.00 TOXICOLOGICAL INFORMATION

Inhalation: **Resin** - Irritation of nose, throat and respiratory tract, fatigue and drowsiness. Higher concentrations will have the following effects loss of consciousness. **Hardener** – LD₅₀ rat > 24.3 mg/l 4 hr exposure time max. **Skin contact:** **Resin** - Modest irritation. Repeated or prolonged exposure may cause dermatitis. **Hardener** – Non irritating. **Eye Contact:** **Resin** – Severe irritant. **Hardener** – Mildly irritating. **Ingestion:** **Resin** – Material is classed as an irritant **Hardener** LD₅₀ (rat) > 5000 mg/Kg.

12.00 ECOLOGICAL INFORMATION

Resin- Do not discharge into drains or the environment.
Hardener – Based on Dibenzoyl peroxide.
Fish acute toxicity, 96h – LC₅₀ >2.0 mg/l (poecilia reticulata)
Bacteria activated sludge respiration inhibition test EC₅₀ = 35mg/l readily biodegradable.

13.00 DISPOSAL CONSIDERATIONS

Resin - Disposal of product and contaminated containers by incineration in accordance with local, state or national regulations only after taking specialist advice. **Hardener** - Disposal of product and contaminated containers by landfill in accordance with local, state or national regulations. Reacted components may be treated as low hazard waste.

14.00 TRANSPORT INFORMATION

Resin - **UN No:** none
Proper Shipping Name: Resin solution, contains methacrylate monomers Not classified as dangerous for transport
Hardener- **UN No:** 3108
Proper shipping name: Organic peroxide Type E Solid(Dibenzyl Peroxide)
ADR/RID Class: 5.2 **Item No.:** 8b

15.00 REGULATORY INFORMATION

Resin-
Classification: Irritant
Risk Phrases: R36/37/38: Irritating to eyes respiratory system and skin.
Safety Phrases: S28: After contact with skin, wash immediately with plenty of soap and water. S36/37/38: Wear suitable protective clothing, gloves and eye/face protection.
Hardener-
Risk Phrases: R7: May cause fire. R36: Irritating to eyes. R43: May cause sensitisation by skin contact.
Safety Phrases: S3/7/9: Keep container tightly closed in a cool ventilated area. S26: In case of contact with eyes, wash immediately with plenty of soap and water. S14: Keep away from reducing agents e.g. amines, acids, alkalis, heavy metal compounds. S50B: Do not mix with Peroxide accelerators. S50c: Do not mix with reducing agents.

16.00 OTHER INFORMATION

Every effort has been made to ensure that the information contained in this safety data sheet is reliable but we cannot accept any liability for any loss, injury or damage that may result from use of the product. This information does not constitute assessment of risk as required by health and safety legislation. Data given in this safety data sheet are solely for guidance in safe handling and use of the product by customers; they do not form part of any specification.

ABCD 494 ISSUE: 1
ISSUED: NOV 2000