

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP 1110, COMP A  
MT1110\_A  
**Revision :** 10.06.2005      **Version :** 4.0.1  
**Print date :** 01.07.2005

---

## 01. Identification of substance, preparation and company

### Product name:

MASTERTOP 1110, COMP A (380-2207-7032) (MT1110\_A)

### Manufacturer/Supplier

Degussa Construction Chemicals  
(Schweiz) AG Division CONICA Technik

### Street/P.O.Box

Industriestrasse 26 /

### Country code/Postal code/Town/City

CH-8207 Schaffhausen

### Telephone / Telefax

+41-52-644-2525 / +41-52-644-2699

### Emergency information

Schweizer Toxzentrum +0041-1-2515151 (CH)  
Centre Anti - Poison +0033 01 40 37 04 04 (FR)  
Toxikologické informa-ní st-edisko +00420 224 919 293 (CZ)  
Myrkytystietokeskus puh.(suora) +358 (0) 9 471 977 (vaihde) 094711 (FIN)

---

## 02. Composition/information on ingredients

### Chemical characterization

Modified epoxide resin

### Hazardous components

REACTION PRODUCT: BISPHENOL F-EPOCHLORHYDRIN MG < 700 ; CAS-No. : 9003-36-5

Percentage : 25 - 50 %

Classification : N ; R 51/53 R 43 Xi ; R 36/38

POLYPROPYLENE GLYCOL DIGLYCIDYL ETHER ; CAS-No. : 9072-62-2

Percentage : 2,5 - 10 %

Classification : R 43 Xi ; R 36/38

2-CHLORACETAMIDE ; EC-No. : 201-174-2 ; CAS-No. : 79-07-2

Percentage : 0,1 - 0,5 %

Classification : Repr. Cat.3 ; R 62 T ; R 25 R 43

---

## 03. Hazards identification

### Hazard designation

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. · May cause sensitisation by skin contact · Irritating to eyes and skin

Classification : N ; R 51/53 · R 43 · Xi ; R 36/38

### Additional information

The product sensitizes the skin. It is skin irritating as well and repeated contact can increase this effect. The product is water polluting.

---

## 04. First-aid measures

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP 1110, COMP A  
MT1110\_A  
**Revision :** 10.06.2005      **Version :** 4.0.1  
**Print date :** 01.07.2005

---

## After inhalation

Take the casualty into the fresh air and keep warm. Keep at rest. Irregular breathing/no breathing: artificial respiration.  
Unconsciousness: lateral position - call a physician.

## After skin contact

Immediately remove all contaminated clothing. Wash away with soap and water and rinse. Do NOT use solvents or thinners.

## After eye contact

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician.

## After ingestion

Contact a doctor immediately. Keep at rest. Do not induce vomiting.

---

## 05. Fire-fighting measures

### Suitable extinguishing media

Alcohol resistant foam, CO<sub>2</sub>, powders, water spray.

### Unsuitable extinguishing media

Waterjet.

### Special risk posed by the substance or by the actual preparation, its combustion products or gases discharged

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

### Special protective equipment

Appropriate breathing apparatus may be required.

### Additional information

Cool endangered containers with water in case of fire. Do not allow the quenching water into the sewage system.

---

## 06. Accidental release measures

### Personal precautions

Remove ignition sources. Provide for sufficient ventilation. Do not inhale the vapour. Refer to protective measures listed in sections 7 and 8.

### Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

### Methods for cleaning up/collecting

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

---

## 07. Handling and storage

### Information for safe handling

Avoid contact with skin and eyes. Do not eat or drink during work - no smoking. Comply with the health and safety at work laws.

### Information about protection against explosions and fires

No particular measures required.

### Requirements to be met by storerooms and containers

Containers should be kept dry and sealed. Containers which are opened must be carefully resealed and kept upright to prevent

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP 1110, COMP A  
MT1110\_A  
**Revision :** 10.06.2005      **Version :** 4.0.1  
**Print date :** 01.07.2005

---

leakage.

## Information about separation of incompatible products

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

## Further information about storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight.

**Storage class (VCI) :** 10

---

## 08. Exposure controls and personal protection

### Additional information about engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of vapours or particels below the OEL (=Occupational Exposure Limit) , suitable respiratory protection must be worn.

### Personal protective equipment

#### General protective and hygiene measures

Wash hands before breaks and after work.

#### Respiratory protection

If workplace limits are exceeded, a gas mask approved for this purpose must be worn.

#### Hand protection

Butylrubber  $\geq 0,5\text{mm}$   $\geq 480$  min. After washing hands replace lost skin fat by fat containing skin creams. By using other gloves with a lower endurance, change them more often.

#### Eye protection

Use safety glasses.

#### Body protection

Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

---

## 09. Physical and chemical properties

### Image

**Form :** Liquid.  
**Colour :** Coloured.  
**Odour :** Characteristic.

### Relevant safety data

<b>Boiling point / range :</b>	( 1013 hPa )		no data available		
<b>Flash point :</b>		>	100	°C	DIN 53213
<b>Vapour pressure :</b>	( 50 °C )		no data available		
<b>Density :</b>	( 20 °C )	ca.	1,4	g/cm <sup>3</sup>	
<b>Solvent-separation test :</b>	( 20 °C )		inapplicable		
<b>Viscosity :</b>	( 20 °C )		8000	mPa.s	

---

## 10. Stability and reactivity

### Conditions to avoid

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP 1110, COMP A  
MT1110\_A  
**Revision :** 10.06.2005      **Version :** 4.0.1  
**Print date :** 01.07.2005

---

Stable under recommended storage and handling conditions(See section 7).

## Materials to avoid

Be careful of exothermic reactions with amines.

## Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

---

## 11. Toxicological information

### Experience on practice

In case of contact with the product: danger of resorption through the skin, irritation of skin/mucous membranes. Eye contact: irritation. Skin contact: frequent and prolonged skin contact may cause irritation and skin inflammation. Susceptible people may suffer allergic reactions.

### Additional toxicological information

The product was classified in toxicological terms on the basis of the results of the calculation procedure outlined within General Directive on Preparations (1999/45/EC).

---

## 12. Ecological information

### Additional ecological information

#### General ecological information

Do not empty into waters or drains. The product is difficult to biologically degrade.

---

## 13. Disposal considerations

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

### Product

#### Waste key

Disposal Code according to European Waste Catalog (EWC) please specify according to the use of product, e.g.: 080112 Waste from production, formulation, sales and application of paints and varnishes. Old paints and varnishes, not containing organic solvents or any other dangerous material.

Switzerland: Disposal code (VVS): 1650 Waste from paints, varnishes and adhesives without organic phase or solvent

---

## 14. Transport information

### Land transport ADR/RID

#### Classification

<b>Class :</b>	9	<b>Kemlercode :</b>	90
<b>Substance number :</b>	3082	<b>Classification-Code :</b>	M6

LQ 7

#### Proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

#### Hazardous components

REACTION PRODUCT: BISPHENOL F-EPICHLORHYDRIN MG < 700

#### Packaging

<b>Packaging group :</b>	III
<b>Label :</b>	9

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP 1110, COMP A  
MT1110\_A  
**Revision :** 10.06.2005      **Version :** 4.0.1  
**Print date :** 01.07.2005

---

## Maritime transport IMDG/GGVSea

### Classification

**IMDG-Code :** 9      **EmS number :** F-A / S-F  
**UN number :** 3082      **Marine Poll. :** -  
LQ 5 I

### Proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

### Hazardous components

REACTION PRODUCT: BISPHENOL F-EPICHLORHYDRIN MG < 700

### Packaging

**Packaging group :** III  
**Label :** 9

## Air transport ICAO-TI and IATA-DGR

### Classification

**Class :** 9  
**UN number :** 3082

### Proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

### Hazardous components

REACTION PRODUCT: BISPHENOL F-EPICHLORHYDRIN MG < 700

### Packaging

**Packaging group :** III  
**Label :** 9

---

## 15. Regulatory information

### Classification according to EEC directives

#### Danger symbol and danger designation



Xi ; Irritant



N ; Dangerous for the environment

#### Hazard-determining components of labelling

REACTION PRODUCT: BISPHENOL F-EPICHLORHYDRIN MG < 700 ; CAS-No. : 9003-36-5

POLYPROPYLENE GLYCOL DIGLYCIDYL ETHER ; CAS-No. : 9072-62-2

2-CHLORACETAMIDE ; CAS-No. : 79-07-2

#### R-phrases

51/53      Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

43      May cause sensitisation by skin contact

36/38      Irritating to eyes and skin

#### S-phrases

61      Avoid release to the environment. Refer to special instructions/Safety data sheets.



# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP 1110, COMP A  
MT1110\_A  
**Revision :** 10.06.2005      **Version :** 4.0.1  
**Print date :** 01.07.2005

---

62                      Possible risk of impaired fertility.

## Department issuing data sheet

Degussa Construction Chemicals Business Line Performance Flooring.

## Contact

R. Burgos / C. Schmidt

---

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

---