

DATA Sheet



DEGREASANT

USES

For the easy removal of oil, grease, wax, bitumen and other extraneous materials from concrete floors and surfaces prior to the application of the FLEXCRETE REPAIR AND PROTECTION SYSTEM.

ADVANTAGES

- Easy to apply by brush or spray.
- Quickly breaks down and removes contaminants from concrete surfaces.
- Excellent penetration properties.
- Easily removed by flushing with water.
- Contains an anti-bacterial additive.
- Inexpensive per square metre coverage.

PRODUCT DESCRIPTION

FLEXCRETE DEGREASANT is a non-caustic, powerful emulsifiable degreasant designed to remove oil, grease, wax, bitumen and other extraneous materials from a variety of surfaces. In its standard form it can be used on concrete, stone, wood, steel, terrazzo and many other surfaces. It can be diluted by water or a spirit based material.

TECHNICAL DATA (TYPICAL)

Appearance: Pale amber coloured low viscosity liquid with slight haze.

Specific Gravity: 0.828 at 15°C.

Flash Point: 62°C (Closed Cup).

APPLICATION DATA

Application Guide available on request.

Scrape off and remove any excess contamination. Shake drum prior to use. Apply **FLEXCRETE DEGREASANT** and brush well into the surface with a stiff bristle brush. Allow about 10 minutes to react with contaminant before thoroughly washing down surfaces with fresh water. Heavily contaminated surfaces may require repeated application. For light cleaning, material can be diluted with water or spirit before use.

SHELF LIFE

Indefinite in manufacturer's sealed containers.

PACKAGING

25 litre heavy duty plastic containers.

SAFETY DATA

Safety Data Sheet available on request.

12/06



Flexcrete Technologies Limited

Tomlinson Road • Leyland • Lancashire
• PR25 2DY • England

Tel: +44 (0) 845 260 7005 • **Fax:** +44 (0) 845 260 7006

e-mail: info@flexcrete.com

www.flexcrete.com

