

Resi Grease

Demoulding paste which can be applied to complex shapes such as canelures, diamond points etc... using a rag

Properties

Resi Grease is a product developed to deal specifically with the difficult problems arising from delayed demoulding of various products compacted by vibration or turning.

Application

- Demoulding complex shapes
- Demoulding pipes compacted by vibration or turning
- Concrete products moulded on rounds or presses
- Greasing of mould cores
- Bonding of tiles at the bottom of the mould to prevent it moving when the concrete is poured.

Characteristics

Nature	Paste
Colour	Dark brown
Density	Approx 0.9
Penetration	170 - 240

According to NF T 60-140

Application instructions

Spread the grease evenly over the mould using a brush, a paint brush, a rag or a sponge.

Resi Grease can be used with our other mould release oils Mouldol or Demoulux.

Packaging

Please see current price list

Storage

Resi Grease can be stored for 24 months in its original packing.

Precautions

The material should be applied evenly, avoiding application of excess or insufficient product.

When the product is applied with a rag or sponge, protective gloves should be worn.

Health and Safety

For further information consult the Product Safety Data Sheet available for this product.



Important note

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard Conditions for the Supply of Goods and Services, copies of which may be obtained on request. Whilst Fosroc endeavours to ensure that any advice, recommendation, specification of information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation of information given by it.

Fosroc Limited

Drayton Manor Business Park
Coleshill Road, Tamworth,
Staffordshire B78 3TL. UK

telephone:
+44 (0) 1827 262222

fax:
+44 (0) 1827 262444

email:
uk@fosroc.com

www.fosroc.com



Certificate number FM 610