



SAFETY DATA SHEET

1: IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product Name: **CONBEXTRA LJ**

Application: Cementitious grout.

Company: **Fosroc Limited**

Address: Coleshill Road, Tamworth, Staffordshire. B78 3TL

Telephone: 01827 262222 Out of Hours: 01827 265279 Fax: 01827 262444

2: COMPOSITION/INFORMATION ON INGREDIENTS

Composition: portland cements, silica sands, additives.


Hazardous Ingredient(s)	Symbol	Risk Phrases	Other Information	%
Cement (OPC)	Xi	R37/38, R43, R41	Cas No: 65997-15-1 Cas No: Cas No: Cas No: Cas No:	>50

All constituents of this product are listed in EINECS (European Inventory of Existing Commercial Chemical Substances) or ELINCS (European List of New Chemical Substances) or are exempt.



Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

R37/38: Irritating to respiratory system and skin
R41: Risk of serious damage to eyes
R43: May cause sensitisation by skin contact



IRRITANT



4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for several minutes. Obtain medical attention urgently.

Skin: Wash immediately with copious quantities of water. Remove contaminated clothing immediately. Obtain medical advice if skin disorders develop.

Inhalation: Remove from exposure. If feeling unwell obtain medical attention.

Ingestion: Wash out mouth with water. Do NOT induce vomiting. Obtain medical attention.

5: FIRE FIGHTING MEASURES

Suitable Extinguishing Media: None, not flammable.

Special Exposure Hazards: None.

Special Protective Equipment: None.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear rubber boots in addition to the recommended protective clothing.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Decontamination Procedures: Avoid the creation of dust in atmosphere. Gather into containers. Residues may be flushed to drain with large volumes of water. Prior consent must be obtained from the local Water Company if discharged to sewer.

7: HANDLING AND STORAGE

Handling: Avoid creating dust. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid skin and eye contact.

Storage: Store in cool, dry area.

8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:-

Substance	8 Hour TWA	STEL	Source/Other Information
silica, amorphous: total inhalable dust	6 mgm ⁻³	-----	EH 40
respirable dust	2.4 mgm ⁻³		
portland cement: total inhalable dust	10 mgm ⁻³	-----	EH 40
respirable dust	4 mgm ⁻³		

Engineering Control Measures: Atmospheric levels of dust must be maintained within the Occupational Exposure Limit. Where mechanical methods are inadequate or impractical, appropriate personal protective equipment must be used.

Personal Protective Equipment: Impervious gloves (eg PVC). Goggles (Conforming to EN 166) / Safety glasses (Conforming to EN 166). Approved dust mask, conforming to EN 149. Nominal Protection Factor (NPF) to be determined.. Change contaminated clothing and clean before re-use.

9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Granulated powder.

Colour: Grey.

Odour: Odourless.

pH(concentrate):

pH(working dilution): >12

Boiling Point/Range (°C): Not applicable.

Melting Point/Range (°C):

Flash Point (closed, °C): None.

Autoflammability (°C): Not applicable

Viscosity (at 20°C):

Explosive Properties (%):

Oxidising Properties: Not determined

Vapour Pressure (kPa at 20°C):

Relative Density (at 20°C): 1.3 (bulk)

Water Solubility: Partially soluble.

Fat Solubility:

Partition Coefficient (n-octanol/water):

Other data:

10: STABILITY AND REACTIVITY

Stability: Stable.

Conditions to Avoid: Exposure to air. Contamination with water.
Materials to Avoid: Strong acids.
Hazardous Decomposition Products: None.

11: TOXICOLOGICAL INFORMATION

Health Effects

On Eyes: Irritating and may injure eye tissue if not removed promptly.
On Skin: Irritation. See "chronic" effects.
By Inhalation: Irritating to respiratory system. Inflammation of the nasal mucous membrane by exposure to cement dust.
By Ingestion: May cause irritation of mouth, throat and digestive tract.
Chronic: Respirable dust, if inhaled over a prolonged period, constitute a health hazard. Inhalation of particles of free silica, in the respirable range, can give rise to fibrosis of the lungs. Cement, cementitious grouts and mortars are known to cause both irritant and allergic contact dermatitis. Prolonged skin contact can result in chemical burns.

Other:

12: ECOLOGICAL INFORMATION

Environmental Assessment: Little detailed information is available on the ecological effects of this product, but its overall environmental impact is not regarded as significant
Mobility: Partially soluble in water.
Persistence and Degradability: Not readily biodegradable.
Bioaccumulative Potential: Not expected to be bioaccumulative.
Ecotoxicity: Not expected to be ecotoxic to fish/daphnia/algae in cured state.

13: DISPOSAL CONSIDERATIONS

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose of in an approved manner.
Used/Contaminated Product: As for Unused product.
Packaging: The method of disposal must be acceptable to the local authority.

14: TRANSPORT INFORMATION

This product is NOT classified as dangerous for transport.

UN Number:

IMO: Class: Packing Group: Marine Pollutant:
IATA/ICAO: Class: Packing Group:
ADR: Class: Item:

Transport Name:

Hazchem/Kemler Code:

15: REGULATORY INFORMATION

Hazard Label Data:-

Named Ingredients: cement powders
UN Number:
Symbol(s): Xi
Risk Phrases: R37/38: Irritating to respiratory system and skin.
R41: Risk of serious damage to eyes
R43: May cause sensitisation by skin contact

