

ACCELERATOR FOR Rofaplast[®] PUR INJECTION RESIN



Article No. 0947

Special accelerator for Rofaplast PUR Injection Resin

Property profile:

In cases of strong water inrush, the reaction time of Rofaplast PUR Injection Resin (Art. No. 0946) can be accelerated by adding Rofaplast Accelerator.

System constituents:

- Rofaplast PUR Injection Resin (Art.No. 0946)
- Accelerator for Rofaplast PUR Injection Resin (Art.No. 0947)

Characteristic data of the product in the packaged state:

Form: liquid
Colour: pink
Density: 0.94 g/cm³
Odour: amine
Viscosity: 15 mPas (20°C)

Working directions:

Add Rofaplast Accelerator for Rofaplast PUR Injection Resin before injecting, stirring the mixture with a suitable mixing tool until it is streak-free.

With a 1% addition of Rofaplast Accelerator to Rofaplast PUR Injection Resin, the reaction time is reduced to approx. 60 seconds.

Packaging, application rate and storing:

Packaging: 50 ml aluminium bottles

Application rate: 10-50 ml Rofaplast Accelerator per 1 kg Rofaplast PUR Injection resin, depending on pressure water.

Shelf-life: At least 6 months in unopened, unmixed, original bottles, stored frost-free

Safety, ecology, disposal:

Further information concerning safety during transport, storage and handling as well as for disposal is found in the latest Safety Data Sheet.

The statements above are compiled from our field of production and according to the latest technological developments and application techniques. Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet.

Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid.

With the publication of this Technical Information Sheet all previous editions are no longer valid.