

Viscacid[®] MATTING AGENT



Article No. 0969

Flat-pieced, mineral matting agent that is blown onto the surface.
A composition of mica, magnesium, aluminium, hydrosilicate and quartz.

Property profile:

Because of its outstanding mineralogical composition, this Matting Agent is inert and has excellent matting and anti-slip properties as a result of its surface structure.
Slip-resistance class R10.

Range of use:

To be used for matting flow coverings and coatings.

Characteristic data of the product in the packaged state:

Density:	2.75 g/cm ³
Hardness:	3-4 (Mohs' scale)
pH value:	7.3 DIN 53200
Ignition loss:	7%
Water content:	max. 0.2%

Working instructions:

Viscacid Matting Agent is blown over the fresh covering with a low pressure or sand blasting gun. The proper moment must

be chosen so that the material bonds to the surface but does not sink into the coating.

Tools:

Flake gun, sandblasting gun, low pressure gun.

Packaging, application rate and storing:

Packaging: 25 kg paper bags

Application rate: 50 - 100 g/m²

Shelf-life: At least 12 months stored in original containers.

Safety, ecology, disposal:

Further information concerning safety during transport, storage and handling as well as for disposal is found in the latest Safety Data Sheet.

The statements above are compiled from our field of production and according to the latest technological developments and application techniques. Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet.

Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid.

With the publication of this Technical Information Sheet all previous editions are no longer valid.