

Technical Information Sheet

Aidol® Anti-Insect

Art. No. 2059-60

Liquid, controlling wood preservative.



Mark of quality:

Aidol Anti-Insect has been awarded the "RAL Wood Preservative" mark of quality after official evaluation of its efficacy against wood pests and after official evaluation of its safety regarding health and the environment when used properly. RAL Award Certificate No. 127.

Property profile:

Aidol Anti-Insect is an agent used to control insects in wood with a simultaneous preventive effect against infestation with insects according to DIN 68 800, part 4.

Range of use:

This product is used to treat furniture and other small wood objects. Do not use on wood that will come in contact with food or animal feed or on large areas (max. 2-3 m²) in indoor areas.

Directions:

Aidol Anti-Insect should be applied by brush. Sand or strip old coatings and clean the surface of the wood. Dispose of the remains from cleaning properly. At least 2 coats of Aidol Anti-Insect should be applied with a brush. Wipe off excess material with an absorbent rag so that polishes and coatings can be applied without harm.

Notes:

Wear protective gloves made of nitrile rubber (NBR). Take off saturated clothing immediately. Use only in well ventilated areas. Do not use in the immediate vicinity of aquatic environments. The product should never be allowed to reach aquatic environments. Wood preservatives contain biocidal ingredients to protect wood from pests. They should only be used according to directions and only in the approved application areas. Misuse may harm health and the

environment. The "Code of Practice for Handling Wood Preservatives" issued by the German industrial association, Deutsche Bauchemie e.V., gives comprehensive information.

Tools and cleaning:

Clean tools immediately after use with a brush cleaner and dispose of the remains from cleaning properly.

Application rate:

300 - 350 ml/m²

Drying:

Depends on the ambient climate. Initially dry after 24 hours with good ventilation. High humidity and lower temperatures delay drying. Scumbles and varnishes can be applied at the earliest after one week.

Active ingredients:

0.02% deltamethrine

100 ml of this product contain 0.016 g deltamethrine.

Storage:

Store dry and frost-free in closed containers.

Quality control:

The quality of our wood preservatives is controlled according to RAL Quality and Testing Provisions RAL GZ 830.

Technical Information Sheet

Characteristic data of the product:

Density: approx. 0.80 g/cm³ at +20 °C
Odour: weak, characteristic
Flash point: approx. 63 °C
Packaging: 250 ml and 750 ml tin cans
Colours: 2059 colourless, 2060 brown

Safety information:

Danger warnings:

Harmful: May cause lung damage if swallowed.
Repeated contact may dry skin out and cause cracked skin.

Safety advice:

Keep out of reach of children.
Keep away from food, beverages and animal feed.
Do not eat, drink or smoke when working.
Avoid contact with skin.
If swallowed, do not induce vomiting. Call a doctor immediately and show label or container.

Product Code: HSM-LB 30

Disposal:

Larger quantities of leftover product should be disposed of in the original containers in compliance with valid regulations. Completely empty containers may be recycled.

Refuse Code No.: 03 02 05 other wood preservatives that contain hazardous substances.

Ecology:

Do not lead into aquatic environments, the sewer system or the ground.
Water hazard class (WGK): 2

Labelling:

Regulations on hazardous substances: Xn Harmful
GGVSE/ADR: -/-

The statements above are compiled from our field of production and according to the latest technological developments and application techniques. Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet.

Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid.

With the publication of this Technical Information Sheet all previous editions are no longer valid.