



# Ronadeck PU Coating & PU Coating WB

## Polyurethane and water based polyurethane floor and wall sealer

### FEATURES

- ✓ clear polyurethane coating
- ✓ in surface sealer for walls and floors
- ✓ suitable for internal and external use
- ✓ increased abrasion and frost resistance
- ✓ improved chemical resistance
- ✓ 2 or 3 coat application
- ✓ UV stable

### SPECIFICATION CLAUSES

#### 1. In surface sealer for walls and floors using PU Coating

The sealer shall be Ronadeck PU Coating by Ronacrete Ltd, telephone +44 (0) 1279 638700. All materials to be applied in accordance with manufacturers instructions.

#### 2. In surface sealer for walls and floors using PU Coating WB

The sealer shall be Ronadeck PU Coating WB by Ronacrete Ltd, telephone +44 (0) 1279 638700. All materials to be applied in accordance with manufacturers instructions.

### SUMMARY APPLICATION PROCEDURE

1. prepare surfaces
2. apply two coats of Ronadeck PU Coating or PU Coating WB
3. apply third coat if necessary

### Description

Ronadeck PU Coating is a clear polyurethane sealer for use on floor and wall surfaces suitable on internal and external concrete, masonry and other substrates. Two grades are available.

### Ronadeck PU Coating

Ronadeck PU Coating is a solvented polyurethane single component moisture curing coating which offers superior abrasion, chemical and weather resistance and of the two grades is the preferred coating in all locations. It is UV resistant, non-yellowing. The cure time can be accelerated; see Table 2.

### Ronadeck PU Coating WB

Ronadeck PU Coating WB is a water based polyurethane coating which should be used when low odour is more important than high performance. It is UV resistant, non-yellowing.

### Uses

Ronadeck PU Coating is used to seal, bind and protect porous substrates. Used as a two coat seal the following benefits can be achieved:

- excellent weathering resistance
- increased anti-abrasion properties
- dust elimination due to in-surface seal
- improve frost resistance of concrete
- chemical resistant against a wide range of chemicals and solvents - consult the Ronacrete Technical Department

### Advantages

- simple to use
- apply by roller
- supplied ready to use
- moisture curing

### Limitations of use

- must not be applied onto wet surfaces
- do not use Ronadeck PU Coating near naked flame
- protect from rain and adverse weather until fully cured
- adhesion is reduced on non-porous surfaces such as glazed tiles

### Surface Preparation

Thoroughly clean all surfaces to remove loose material, dirt, dust, grime etc. Remove any standing water to leave the surface as dry as possible. Any moss, algae or fungal growth should be treated with Fongimousse Plus followed by hosing and stiff brushing.

### Method of Application

1. Ronadeck PU Coating is supplied ready to use; no dilution is required.
2. apply by roller to ensure a complete membrane is formed without breaks or pinholes.
3. apply evenly, recognising that uneven application marks result in visible roller marks and shading
4. two coats are normally sufficient although 3 coats may be needed on very porous substrates. Allow a minimum 4 hours between coats.
5. avoid pooling, ponding and over-treating as this will create a surface glaze.
6. when attempting to consolidate porous and friable surfaces such as screeds or renders, apply successive coats to satisfy the porosity of the surface and until no more is absorbed. The degree to which such surfaces can be improved is variable and dependent on factors including the make up of the surface, the size and nature of pores, the original strength and stability of the surface. Application of this type is not always successful.

### Coverage

Coverage is shown in Table 1. Note that coverage rates quoted are theoretical and based on application on to smooth non-porous surfaces; actual coverage rates can be assessed only by practical trials on representative areas of the structure and these are recommended in all situations, especially where surfaces are rough texture and / or porous.

### Health and Safety - Ronadeck PU Coating

Do not apply Ronadeck PU Coating by spray gun or in confined spaces unless wearing appropriate breathing apparatus.

Ronadeck PU Coating is flammable - contents have a flashpoint of 32°C. Avoid naked flames. Ronadeck PU Coating is classified as an irritant. Avoid inhalation of fumes and skin or eye contact.

Wear rubber overalls, goggles and gloves; use barrier cream and breathing apparatus if required by working conditions. In the event of fire use foam, dry chemical carbon dioxide extinguishers or water fog appliances.

### Health and Safety - Ronadeck PU Coating WB

Ronadeck PU Coating WB is not classified as hazardous. If spraying wear particle mask and provide adequate ventilation in confined spaces.

Wear cotton/synthetic overalls, goggles and gloves; use barrier cream and breathing apparatus if required by working conditions. In the event of fire use foam, dry chemical carbon dioxide extinguishers. Ronadeck PU Coating/WB is not flammable.

Please refer to separate Health and Safety data sheets.

### First aid

In the event of skin contact wash immediately with soap and water for 15 minutes. Seek medical attention if necessary. For eye contact wash immediately with copious quantities of water. Seek immediate medical advice. If ingested wash mouth thoroughly with water. Induce vomiting. Seek immediate medical advice.

### Spillage

Wash small spills away with water; soak large spills with earth or sand. Avoid contact; inform authorities if major spillage occurs.

### Storage

Shelf life is 12 months. Replace lid immediately after use. Once opened use the material within 2 days. Store in a cool, dry place.

## Ronadeck PU Coating - Polyurethane and water based polyurethane floor and wall sealer

### Supply

Ronadeck PU Coating is supplied in 5 litre cans and 25 litre drums.

### Site Attendance

When on site Ronacrete representatives are able, if asked, to give a general indication of the correct method of installing a Ronacrete product. It is important to bear in mind that Ronacrete Ltd is a manufacturer and not an application contractor and it is therefore the responsibility of the contractor and his employer to ensure he is aware of and implements the correct practices and procedures to ensure the correct installation of the product and that liability for its correct installation lies with the contractor and not with Ronacrete Ltd.

Table 1 Technical Data at 20°C. All times are approximate and will vary according to site conditions including substrate, temperature and air movement.		
	Ronadeck PU Coating	Ronadeck PU Coating WB
Coverage (approx.)	8-10m <sup>2</sup> per litre per coat	8-10m <sup>2</sup> per litre per coat
Number of coats	2 or 3	2 or 3
Touch dry	4 hours	4 hours
Re-coatable	7 hours	4 - 16 hours
Full cure	24 hours	24 hours
Flash point	32°C	> 100°C
Application temperature range	5°C to 25°C	10°C to 25°C
Shelf life	12 months in unopened containers	12 months in unopened containers
Taber Abraser ASTM D4060	31 milligrams	92 milligrams
Abrasion resistance after 1000 cycles	65 milligrams	160 milligrams

Table 2 The use of Ronadeck PU Coating Accelerator to speed cure and reduce traffic times Note: not for use with WB		
Time to foot traffic and to apply subsequent coats	Ronadeck PU Coating without catalyst	Ronadeck PU Coating with catalyst
@ 20°C	2 hours	2 hours
@ 15°C	5 hours	3 hours
@ 10°C	8 hours	4 hours

- Rate of addition is 1% by weight of Ronadeck PU Coating.
- Accelerator is supplied as a liquid.
- To use, measure accurately and add to Ronadeck PU Coating.. Stir by hand or with a very slow speed drill and paddle for 30 seconds. Do not entrain air or create air bubbles.
- Add immediately before use.

RONL 133 Issue 7 4 July 2007

The information detailed in this leaflet is liable to modification from time to time in the light of experience and of normal product application, and before using, customers are advised to check with Ronacrete Ltd, quoting the reference number, that they possess the latest issue. Any person or company using the product without first making further enquiries as to the suitability of the product for the intended use does so at his own risk, and Ronacrete Ltd can accept no responsibility for the performance of the product, or for any loss or damage arising out of such use. All goods supplied subject to our Terms and Conditions of Sales; see [www.ronacrete.co.uk](http://www.ronacrete.co.uk).



Ronacrete Ltd, Ronac House, Flex Meadow, Merring Way, Harlow, Essex CM19 5TD, U.K.  
Tel: +44 (0)1279 638700 [www.ronacrete.co.uk](http://www.ronacrete.co.uk) [technical@ronacrete.co.uk](mailto:technical@ronacrete.co.uk)