



IKO PLC
 Technical & Design Services – Roofing
 Coney Green Road, Clay Cross, Chesterfield,
 Derbyshire, S45 9HZ
 Tel: 0844 412 7228 Fax: 0844 412 7229
 E-Mail: technical@ikogroup.co.uk

Bitumen Paint

02401720



www.ikogroup.co.uk

PROTECTIVE BITUMEN PAINT

DESCRIPTION:

- General-purpose bitumen paint that provides protection for a range of substrates including iron, steel, concrete, brickwork, fibre cement and zinc.
- Provides protection for all outdoor constructions below ground or in contact with the ground.

USE:

- All types concrete and brickwork, construction plinths, septic tanks, drainpipes, wooden garden posts, concrete, metal, reservoirs, railway sleepers, drainage channels etc
- Ideal protection for all materials in contact with groundwater.

NOTE:

- In common with all bitumen paints, IKOpro Bitumen Paint weathers to a matt black finish, and cannot be overcoated with conventional oil based paints.
- Do not apply to surfaces previously treated with a tar based product.
- Drying times may be extended during low temperatures.

APPLICATION:

- Application temperature should be between +3 and +27°C.
- IKOpro Bitumen Paint is ready for use and should not be thinned.
- The substrate needs to be sound, fixed, clean and free of dust and rot.
- Loose or blistered existing paint finishes should be removed.
- Prime iron and steel surfaces with a suitable rust inhibiting primer, which must be thoroughly dry before over painting.
- Galvanised surfaces should be roughened with a wire brush or treated with a suitable etching primer.
- Apply by brush, a minimum of two coats recommended. Allow each coat to dry 2-4 hours before applying the next.

COVERAGE:

- Metal surfaces: 8-10 m²/Litre per coat
- Concrete and timber: 4-6 m²/Litre per coat

CLEANING:

- White Spirit

PACKAGING:

- 5L & 25L cans

TYPICAL PROPERTIES:

| | |
|----------------------------------|-------------|
| Solid contents w/w | approx. 50% |
| Relative density at 15°C | 0.91 – 0.93 |
| Drying time at 15°C | 2 – 4 hours |
| Flash point (Abel closed cup) °C | minimum 32 |

STORAGE:

- Containers should be kept sealed in a cool, dry, well ventilated environment and all practical precautions taken against fire.
- Partly used containers may be resealed and used again after correct storage.
- To avoid the risk of spillage, always store and transport in a secure upright position.

SHELF LIFE

- Maximum 3 years in sealed container.

HEALTH AND SAFETY:

- Keep container tightly sealed and away from direct heat. Keep away from sources of ignition. No smoking. Avoid contact with skin and eyes.
- Should there be contact with skin, wash immediately with soap and water or a recognised skin cleaner. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In the event of accidents, seek medical attention immediately.
- Do not empty into drains.
- Do not allow solvent vapour to enter the air intakes of the ventilation systems of buildings.

FIRE:

- In case of fire, use foam, dry powder, carbon dioxide or sand. Never use water jet.

