



IKO PLC
Technical & Design Services – Roofing
Coney Green Road, Clay Cross, Chesterfield,
Derbyshire, S45 9HZ
Tel: 0844 412 7228 Fax: 0844 412 7229
E-Mail: technical@ikogroup.co.uk

Cold Bitumen Adhesive

02401310



www.ikogroup.co.uk

BITUMEN ADHESIVE FOR PARTIAL BONDING

DESCRIPTION:

- Cold applied adhesive for partial bonding of insulation panels or vapour control layers to a variety of substrates.

USE:

- As an insulation adhesive.
- For application on roofs below 10° pitch
- **Only under ballasted roofing systems.**

APPLICATION:

- Application temperature should be between +3 and +27°C.
- All surfaces must be clean, dry and free from grease, oil, dirt and loose material.
- Apply the IKOpro Cold Bitumen Adhesive in spots and press the insulation boards firmly into position.
- Porous surfaces may require priming with a coat of IKOpro Bitumen Primer and allowed to dry before proceeding.

COVERAGE:

- Depends on the substrate and on the size of the insulation panels.
- Approximately 750 g/m² in general.

CLEANING:

- White Spirit.

PACKAGING:

- 25kg metal container.

STORAGE:

- Keep containers tightly closed when not in use. Store in dry conditions. To avoid the risk of spillage, always store and transport in a secure upright position.

SHELF LIFE:

- 3 years in sealed packaging.

HEALTH AND SAFETY:

- Keep container tightly sealed and away from direct heat. Keep away from sources of ignition. No smoking. Avoid contact with skin and eyes. Should there be contact with skin, wash immediately with soap and water or a recognised skin cleaner. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In the event of accidents, seek medical attention immediately. Do not empty into drains. Do not allow solvent vapour to enter the air intakes of the ventilation systems of buildings.

FIRE:

- In case of fire, use foam, dry powder, carbon dioxide or sand.
Never use water jet.

