

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Code</b>	SKD100A
<b>Product Name</b>	Sikadur-100 Part A
<b>Product Description</b>	Two component thixotropic adhesive based on epoxy resin.
<b>Manufacturer/Supplier</b>	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444 Fax. 01707 329129

**2. COMPOSITION/INFORMATION ON THE COMPONENTS****Preparation - Hazardous ingredients ( Europe )**

<b>Component</b>	<b>CAS/EINECS</b>	<b>Concentration</b>	<b>Classification</b>	<b>Risk Phrases</b>
Epoxy resin ( No.Av. mol.wt. < 700)	25068-38-6	10.00% - 25.00%	Xi, N	R36/38, R43, R51/53
Aliphatic glycidyl ether	68609-97-2	1.00% - 2.50%	Xi, N	R38, R43, R51/53

**3. HAZARD IDENTIFICATION**

<b>Main Hazards</b>	Irritating to eyes and skin. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
---------------------	---

**4. FIRST AID MEASURES**

<b>Eye Contact</b>	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention urgently.
<b>Skin Contact</b>	Wipe off as much as possible with a clean dry cloth. Wash skin thoroughly with soap and water. If material proves difficult to remove, use suitable skin cleanser (not solvent). Solvents should not be used to clean skin because they may increase the penetration of the material. Obtain medical attention if blistering occurs or redness persists.
<b>Ingestion</b>	Wash out mouth with water. Obtain medical attention.
<b>Inhalation</b>	Remove from exposure. In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure, obtain medical attention.

**5. FIRE FIGHTING MEASURES**

<b>Extinguishing Media</b>	Not readily combustible. Use foam, dry chemical or carbon dioxide.
<b>Extinguishing Media - Not suitable</b>	Do not use water jet.
<b>Special Hazards of Product</b>	Combustion will produce smoke, carbon dioxide and carbon monoxide.
<b>Protective Equipment for Fire-Fighting</b>	Wear full protective clothing and self-contained breathing apparatus.



# SAFETY DATA SHEET

## Sikadur-100 Part A

Date of issue - 30/06/2005.

SKD100A

### 6. ACCIDENTAL RELEASE MEASURES

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Try to prevent the material from entering drains or water courses.
<i>Spillages</i>	Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

### 7. HANDLING AND STORAGE

<i>Handling</i>	Exposure by inhalation or skin contact should be minimised by good Industrial Hygiene practices. Avoid contact with eyes, skin and clothing. Use in well ventilated area.
<i>Storage</i>	Storage area should be: cool. dry. Storage temperature should be controlled to between 5 and 25 °C. Store in the original container securely closed . Keep away from foodstuffs

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<i>Engineering Control Measures</i>	Use of the basic principles of Industrial Hygiene will enable this material to be used safely.
<i>Respiratory Protection</i>	Respiratory protection not normally required.
<i>Hand Protection</i>	Wear suitable impervious gloves. (butyl / nitrile type)
<i>Eye Protection</i>	Wear safety glasses if risks of accidental contamination are possible during application.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<i>Physical State</i>	Paste.
<i>Color</i>	Off-white.
<i>Odor</i>	Characteristic.
<i>Flash Point °C</i>	Not applicable.
<i>Solubility - Water</i>	Insoluble.
<i>Density (kg/m<sup>3</sup>)</i>	Approx. 1800 - 1900 at 20 °C.
<i>Viscosity (at 20°C)</i>	Thixotropic paste

### 10. STABILITY AND REACTIVITY

<i>Stability</i>	Stable under normal conditions.
<i>Hazardous Decomposition Products</i>	Combustion will generate: oxides of carbon. acrid smoke and irritating fumes.

### 11. TOXICOLOGICAL INFORMATION

<i>Acute toxicity</i>	Low order of acute toxicity.
<i>Eye irritation</i>	Irritating to the eyes.
<i>Skin irritation</i>	Frequent or prolonged skin contact may cause some local short term skin irritation.
<i>Sensitization - Skin</i>	The low molecular weight epoxy resin is a potential skin sensitiser. The possibility of allergic sensitisation should be considered.



# SAFETY DATA SHEET

## Sikadur-100 Part A

Date of issue - 30/06/2005.

SKD100A

### 12. ECOLOGICAL INFORMATION

<i>Mobility</i>	The product is insoluble in water.
<i>Persistence/degradability</i>	The product is expected to be not readily biodegradable.
<i>Ecotoxicity</i>	This material is harmful to aquatic organisms.


### 13. DISPOSAL

<i>Product Disposal</i>	Hazardous waste. Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty containers may contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

### 14. TRANSPORT INFORMATION

<i>ADR/RID : Proper shipping name</i>	Not Regulated under ADR/RID
<i>IMDG : Proper shipping name</i>	Not Regulated under IMDG
<i>IATA : Proper shipping name</i>	Not Regulated under ICAO

### 15. REGULATORY INFORMATION

<i>Label Requirements</i>	Irritant, Dangerous for the environment 
<i>Risk Phrases</i>	Irritating to eyes and skin. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<i>Safety Phrases</i>	Avoid contact with skin. Wear suitable gloves.  Contains epoxy constituents. See information supplied by the manufacturer.
<i>Contains</i>	reaction product: bisphenol A-(epichlorhydrin) epoxy resin (no av. mol wt <= 700) oxirane, mono[(C12-14-alkyloxy)methyl]derivs.

### 16. OTHER INFORMATION

<i>First Issue Date</i>	14.06.2004
<i>Revisions Highlighted</i>	Composition / information on ingredients Main Hazards Regulatory Information
<i>Uses and Restrictions</i>	Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.



## SAFETY DATA SHEET

### Sikadur-100 Part A

Date of issue - 30/06/2005.

SKD100A

---

#### *UK Legislation*

Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions.

SI 2002/1689: Chemicals (Hazard Information and Packaging) Regulations

SI 2002/2677: The Control of Substances Hazardous to Health Regulations

SI No. 972/1996: The Special Waste Regulations 1996

SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.

#### *UK Guidance Publications*

Approved Code of Practice - Management of Health and Safety at Work, HSE.

General Approved Code of Practice to COSHH Regulations, HSE.

#### *Footnote*

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Code</b>	SKD100B
<b>Product Name</b>	Sikadur-100 Part B
<b>Product Description</b>	Two component thixotropic adhesive based on epoxy resin
<b>Manufacturer/Supplier</b>	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444 Fax. 01707 329129

**2. COMPOSITION/INFORMATION ON THE COMPONENTS****Preparation - Hazardous ingredients ( Europe )**

<b>Component</b>	<b>CAS/EINECS</b>	<b>Concentration</b>	<b>Classification</b>	<b>Risk Phrases</b>
Triethylenetetramine	112-24-3	2.50% - 10.00%	C	R21, R34, R43, R52/53
Benzyl Alcohol	100-51-6	2.50% - 10.00%	Xn	R20/22
Solvent Naptha (petroleum) heavy aromatic. bp > 240°C	64742-94-5	1.00% - 2.50%	Xn, N	R51/53, R65, R66, R67

**3. HAZARD IDENTIFICATION**

<b>Main Hazards</b>	Irritating to eyes and skin. May cause sensitization by skin contact.
---------------------	--

**4. FIRST AID MEASURES**

<b>Eye Contact</b>	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Eyelids should be held away from the eyeball to ensure thorough rinsing. Obtain medical attention urgently.
<b>Skin Contact</b>	Wipe off as much as possible with a clean dry cloth. If material proves difficult to remove, use suitable skin cleanser (not solvent). Solvents should not be used to clean skin because they may increase the penetration of the material. Contaminated clothing should be washed or dry-cleaned before re-use.
<b>Ingestion</b>	Do not induce vomiting. Obtain medical attention urgently.
<b>Inhalation</b>	Remove from exposure. In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure, obtain medical attention.

**5. FIRE FIGHTING MEASURES**

<b>Extinguishing Media</b>	Not readily combustible. Use foam, dry chemical or carbon dioxide.
<b>Extinguishing Media - Not suitable</b>	Do not use water jet.
<b>Special Hazards of Product</b>	Combustion will generate oxides of carbon and nitrogen
<b>Protective Equipment for Fire-Fighting</b>	Wear full protective clothing and self-contained breathing apparatus.



# SAFETY DATA SHEET

## Sikadur-100 Part B

Date of issue - 30/06/2005.

SKD100B

### 6. ACCIDENTAL RELEASE MEASURES

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Try to prevent the material from entering drains or water courses.
<i>Spillages</i>	Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

### 7. HANDLING AND STORAGE

<i>Handling</i>	Avoid contact with eyes, skin and clothing. Mix in a well ventilated area.
<i>Storage</i>	Storage area should be: cool. dry. Storage temperature should be controlled to between 5 and 25 °C. Store in the original container securely closed . Keep away from foodstuffs

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<i>Engineering Control Measures</i>	Use of the basic principles of Industrial Hygiene will enable this material to be used safely.
<i>Respiratory Protection</i>	Respiratory protection not normally required.
<i>Hand Protection</i>	Wear suitable impervious gloves. (butyl / nitrile type) The insides of gloves must be kept scrupulously clean.
<i>Eye Protection</i>	Chemical goggles.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<i>Physical State</i>	Paste
<i>Color</i>	Grey.
<i>Odor</i>	Ammoniacal.
<i>Flash Point °C</i>	Not applicable.
<i>Solubility - Water</i>	Insoluble
<i>Density (kg/m3)</i>	Approx. 2000 - 2200 at 20 °C.

### 10. STABILITY AND REACTIVITY

<i>Stability</i>	Stable under normal conditions.
<i>Hazardous Decomposition Products</i>	Heating may produce: ammonia. oxides of carbon. oxides of nitrogen. ammonia. acrid smoke and irritating fumes.

### 11. TOXICOLOGICAL INFORMATION

<i>Acute toxicity</i>	Low order of acute toxicity.
<i>Eye irritation</i>	Irritating to the eyes.
<i>Skin irritation</i>	Prolonged contact may cause irritation.
<i>Sensitization - Skin</i>	The possibility of allergic sensitisation should be considered.



# SAFETY DATA SHEET

## Sikadur-100 Part B

Date of issue - 30/06/2005.

SKD100B

### 12. ECOLOGICAL INFORMATION

<i>Mobility</i>	insoluble in water.
<i>Persistence/degradability</i>	The product is expected to be not readily biodegradable.
<i>Ecotoxicity</i>	This material is harmful to aquatic organisms.

### 13. DISPOSAL

<i>Product Disposal</i>	Dispose of as Special Waste. Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty containers may contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

### 14. TRANSPORT INFORMATION

<i>ADR/RID : Proper shipping name</i>	Not Regulated under ADR/RID
<i>IMDG : Proper shipping name</i>	Not Regulated under IMDG
<i>IATA : Proper shipping name</i>	Not Regulated under ICAO

### 15. REGULATORY INFORMATION

<i>Label Requirements</i>	Irritant 
<i>Risk Phrases</i>	Irritating to eyes and skin. May cause sensitization by skin contact.
<i>Safety Phrases</i>	Avoid contact with skin. Wear suitable gloves.
<i>Contains</i>	3,6-diazaoctanethylenediamine

### 16. OTHER INFORMATION

<i>First Issue Date</i>	14.06.2004
<i>Revisions Highlighted</i>	Composition / information on ingredients
<i>Uses and Restrictions</i>	Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.
<i>UK Legislation</i>	Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions. SI 2002/1689: Chemicals (Hazard Information and Packaging) Regulations SI 2002/2677: The Control of Substances Hazardous to Health Regulations SI No. 972/1996: The Special Waste Regulations 1996 SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.
<i>UK Guidance Publications</i>	Approved Code of Practice - Management of Health and Safety at Work, HSE. General Approved Code of Practice to COSHH Regulations, HSE.



## SAFETY DATA SHEET

### Sikadur-100 Part B

Date of issue - 30/06/2005.

SKD100B

---

**Footnote**

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.