


FlexGel Hydrophilic NSF LV Gel



SealBoss® FlexGel System Applications

- Stop Water Infiltration
- Curtain & Bladder Injection Methods
- Sewers, Manholes, Utility Boxes, Tunnels, Dams
- Sealing Joints, Pipe joints, Pipe Intrusions
- Soil Stabilization

Water Activated, Flexible, Hydrophilic Injection Gel / Foam

- SealBoss® Product-Pump-Packer System Solution
- NSF/ANSI 61 Potable Water Contact Approved
- Unregulated For Transport
- Advanced MDI Formulation
- This Product is for Professional Use

Product Description

SealBoss® FlexGel is a low-viscosity, single component hydrophilic polyurethane grout offering excellent penetration properties, superior strength and durability.

At a mixing ratio of 1 part FlexGel to 10 parts water by volume, the mixed product has a super low viscosity of 50 cps. The product is capable of incorporating large amounts of water into itself, thereby forming a waterproofing gel. The ability of FlexGel to swell and increase in volume due to water absorption is one of the important features that differentiate hydrophilic grouts from their hydrophobic counterparts. SealBoss® FlexGel is certified for water contact in accordance with NSF standard 61, for contact with potable water.

SealBoss® FlexGel can either react to a foam or a gel on contact with water based on the mixing ratio. The product forms a flexible gel at product to water ratios from 1:4 to 1:15. Less water results in a stronger gel. The gel time is about 1 to 3 minutes varying with temperature and water saturation. At low product to water ratios of 1:1 to 1:2 SealBoss® FlexGel reacts to a flexible and closed cell foam under pressure. To achieve most satisfying and permanent results, a combination of SealBoss® FlexGel with other systems of our product line may be advised. Ask your SealBoss technician for details. The product is for professional use.

Installation Guidelines

Multi ratio pump : For best results SealBoss® FlexGel should be injected with a multi ratio pump at preset product to water ratio to achieve the desired gel consistency and properties.

Single component pump: The product may also be applied with single component injection equipment. The presence of sufficient water in the substrate is necessary for the product to form a gel. It may be advisable to introduce water prior to injection. In areas of very little water content and little counter pressure the product may expand to a foam.

For curtain / bladder injection methods behind below grade structures it is recommended to drill through the structure in a pattern that is determined by the physical properties of the soil.

To create a standard checkerboard pattern, holes are drilled 50 cm (two feet) apart from each other in a horizontal line. The next step is to drill holes in a line 50 cm above the first line in the same fashion but staggered. Begin injection at the highest point. Each packer should be injected until material penetrates the surrounding drill holes. Patterns may vary according to conditions on the jobsite.

Drill Pattern for Curtain / Bladder Injection Method



All equipment, pumps and hoses must be dry. Avoid moisture contact with the mixture to prevent premature reaction. If product foams while pumping, immediately shut down the machine and flush with a cleaner to avoid built up and clogging of the equipment.

Maintenance of Equipment

Tools and equipment must be cleaned immediately after use. Remove all excess product. Cured product is hard to remove. **SealBoss® R70 Pump Flush** is a solvent free, non-flammable cleaner, lubricator, pump and hose conditioner. Please refer to the product data sheet for detailed information.


Health and Safety

Protect your health! always use safety gear in compliance with OSHA and all applicable local and job-site regulations While working with products. Handling of this product may result in spills, splashes, and airborne substances. Wear appropriate safety goggles, gloves and safety clothing at all times. During the pressure injection process a full face shield is advised for anybody within reach of product spill or blowout. Consider property in proximity of the application to prevent loss or damage. Protect jobsite from unauthorized persons. Store all materials and equipment safely and out of reach of children and animals! Observe container labels, SDS, applicable laws and regulations and all instructions before using the product and equipment. In case one of the components comes in contact with the skin, wash thoroughly with soap and water. Provide adequate ventilation in volume and pattern in working area. Further protection: emergency showers and eyewash stations. Get immediate medical attention as needed.

FlexGel Hydrophilic NSF LV Gel



TECHNICAL DATA	FLEXGEL2		
Appearance	Amber		
Solids	100%	ASTM D 1010	
Density, g/ml	1.1	ASTM D 3574	
Flash Point, C / F	>225	ASTM D 93-85	
Viscosity Mixed With Water, cps at 75F / 25C			
Water : Gel 10:1	50 cps	ASTM D 1638-74	
Water : Gel 5:1	100 cps	ASTM D 1638-74	
Viscosity Gel Component, cps at 40C-25C 400-500 cps	ASTM D 1638-74		
Corrosiveness	Non-Corrossive		
Solubility in Water	Gel		
Components	Polyurethane Resin		
Packaging	5 Gal 55 Gal		
Storage	1 year, unopened containers at 15° - 30° C 58° - 85° F. Store indoors.		
Induction Time, 20C/68F	<30 sec		
Gel time, 25C/70F	approx. 100 sec		
Properties:			
Physical Form	Foam	Gel	Gel
Water Ratio, approx.	1:1	1:5	1:8
Tensile Strength, psi	430	165	150
Bonding Stregth	300-380	120-150	120-140
Tensile Elongation, %	462	>1250	>1250
Die-C	49	43	43
Shrinkage	<1%-10%		ASTM D1042
	variable with water content & foam or gel reaction		
NSF/ANSI 61 Certified			



Limited Warranty Policy and Disclaimer for Products Supplied and/or Distributed by SealBoss Corp.: SealBoss Corp. Products are for Professional Use. All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use. SealBoss Corp. warrants supplied / distributed products to be free of manufacturing defects. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of the manufacturer which proves to be defective. There are no other warranties by SealBoss Corp. of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. SealBoss Corp. shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. SealBoss Corp. shall not be responsible for use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, UV damage, excessive temperature exposure, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and / or physical movement of the substrate or structural defects are also excluded from the limited warranty. SealBoss Corp. reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations and statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller. SealBoss Corp. reserves the right to change the properties of products without notice.

Revised 201508