

Like thousands of contractors world wide you will be using a SealBoss® quality packer for your injection job. Packers come in many sizes and shapes. Prices range widely and more expensive is always better, plastic may not be as effective as metal and rubber vice versa.

There is a reason for our large selection. The injection method and material properties will determine the hardware. Are your cracks actively leaking, are they dry, do you use epoxy or do you inject polyurethane? How much pressure will be used, how do you connect your grout line?

There are two primary categories of packers available. Insertable packers (mechanical packers) and surface mounted ports. Mechanical packers are typically used for polyurethane injection and high pressure epoxy injection. Since they are not glued to the surface, they work well in wet areas and with decayed 'problem' concrete.

Mechanical packers come with zerk fittings and button heads (slide fittings). The zerk type is more commonly used and is less costly. It easily connects and disconnects and works nicely with medium to high injection pressures. The button head type can be of advantage in high volume applications and it offers a superior connection which is helpful for single operator injection and large applications. Injection pressure is the keyword. To determine a quality packer it must withstand high injection pressures without leaking and moving out of its drill hole. A snug fit and solid connection are mandatory. Nobody likes packers to fail at injection pressures of 1000psi and more. Now, realistically speaking even the best packer may slightly leak at the connection at extreme pressures. But there is the difference between a drip and a gush.

SealBoss® premium packers are mostly made of metal and an expandable rubber sleeve to minimize concrete spalls and packer blow outs. A medium soft, 'made to stick' rubber that evenly expands diameter while compressed provides the best grip. Mechanical packers made of plastic and plastic sleeves are typically at a disadvantage at very high pressures, but may suffice at lower pressure, high volume injection jobs. Keep in mind, a snug and reliable fit is always essential for the safety of the technician and the key factor for successful injection work. Do not compromise safety.



Packers

The size of the packer you need depends on the volume to be pumped, drill depth, injection pressures to be applied as well as cosmetic and other considerations. Common diameters are 1/4inch, 6mm, 3/8 inch, 8mm, 10mm, 1/2 inch, 13mm, 5/8inch, 16mm, and sometimes 3/4 inch or even larger. (In mining applications for example, packers can be several feet long and several inches thick) For concrete injection, typically the 1/2" and 5/8" packer seem to be the best compromise in strength and size and can be called a standard. The smaller 3/8" (10mm) types have been gaining in popularity though. Long versions and extensions are also available. It is good practise to keep the drill-holes rather smaller than larger when selecting your packer size.

Design considerations such as location of an anti return valve, ease of use etc. may be of concern. We generally recommend mechanical type packers for most jobs. Their design can cope with most demands found at an injection job and the 'problem rate' is very low - a packer for all conditions. If high product flow at lower pressures is desired, the 5/8" button head packers achieve good results. The 3/8 Hammer-In packer performs at low pressures in excellent concrete. Precise round drill holes are important for a snug fit. Surface ports are commonly used for epoxy injection at low injection pressures. They are glued to the concrete surface. A spread out base with holes is recommended for good adhesion. The grout line can then be attached with a quick-connect system. Since most surface ports lack an anti return valve, a seal cap is provided for use after injection.

SealBoss® provides unique ports for specialty applications such as a surface port with a zerk fitting to utilize single component injection systems for small epoxy and polyurethane jobs, the injection screw for the SealBoss Inject Tube System 2000 for cold joints and other specialty packers.

SealBoss® is a leading supplier of injection packers. We keep a large inventory of different sizes, shapes, materials and connections. Our great turnover rate permits us to offer packers at the most competitive prices possible. Call us and request your free samples. Get the right packers for your job and save money now!

SealBoss® Packer Info Sheet

Professional Packer & Injection Accessories

13-60S



13-60SB



13-115S



13-175S



16-60S



16-115S



6-46B



8-50B



10-60B



10-100B



13-70B



13-100BB



13-200B



16-70B



13-70ZI



5/8 PLASTIC
BUTTON



WITH



VARIABLE



COUPLERS



3/8" HAM-IN



PLASTIC SURFACE PORT WITH ZERK



EPOXY SURFACE PORT


EPOXY CORNER SURFACE PORT



EPOXY DRILL HOLE HAMMER-IN PORT



Button Head/ Slide Coupler



Zerk Coupler

Ask For Our Heavy Duty Drill Bits



Sizes

S-TYPE

Size	Code	Part Number
1/2" /13mm	x3" (70mm)reg	13-60S
5/8" /16mm	x3" reg	16-60S
1/2" /13mm	x4" long	13-115S
1/2" /13mm	x6" long	13-175S
5/8" /16mm	x4" long	16-115S

B-TYPE

Size	Code	Part Number
1/2" /13mm	x3"	13-70B
5/8" /16mm	x3"	16-70B
3/8" /10mm	x55mm	10-60B
5/16" /8mm	x50mm	8-50B
1/4" /6mm	x46mm	6-46B
1/2" /13mm	x4" (100mm)	13-100B
5/8" /16mm	x4" (100mm)	16-100B
1/2" /13mm	x6" (150mm)	13-150B
5/8" /8mm	x6" (150mm)	16-150B
1/2" /13mm	x8" (200mm)	13-200B
5/8" /8mm	x8" (200mm)	16-200B

ZINK-TYPE

Size	Code	Part Number
1/2" /13mm	x3"	13-70ZI

HW-TYPE

Size	Code	Part Number
1/2" /13mm	x3"	13-70HW
5/8" /16mm	x3"	16-70HW
3/8" /10mm	x3"	10-70HW

Plastic Button-TYPE

Size	Code	Part Number
5/8" /16mm	x4"	5/8BPB

Hammer-In Plastic Packers

size: 3/8" /10mm x3" , code: 3/8 Ham/In

Surface Epoxy Ports

Tri base, Corner & Drill Hole Hammer-In

SealBoss®



13-100 AL