SealBoss 15X

Print date: May 10.2015 Revision date: May 10, 2015 EN Version: 1 Issue date: May 10, 2015 Page 1 / 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifiers

Identification of the substance or mixture: SealBoss 15X

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

polyhydroxy alcohol - amine component for polyurethane foam resin

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

SealBoss Corp.

 1669 E Wilshire Ave.
 Telephone: +1-714-662-4445

 Santa Ana, CA 92705
 Fax: +1-714-662-4446

 United States
 Fax: +1-714-662-4446

Dept. responsible for information:

laboratory

E-mail info@sealboss.com

1.4. Emergency contact information:

ChemTel 1-800-255-3924 OR International: +01-813-248-0585

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Skin Irrit. 2 / H315 skin corrosion/irritation Causes skin irritation.

Eye Dam. 1 / H318 Serious eye damage/eye irritation Causes serious eye damage.

Skin Sens. 1 / H317 respiratory or skin sensitisation May cause an allergic skin reaction.

Classification according to Directive 67/548/EEC or 1999/45/EC

This mixture is classified as hazardous according to 1999/45/EC.

Xi; R36/38 Irritant Irritating to eyes and skin.

R43 May cause sensitization by skin contact.

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms





Danger

Hazard statements

H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of water/.?.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/.?.

contains:

2-[2-(dimethylamino)ethoxy]ethanol

N-[2-[2-(dimethylamino) ethoxy] ethyl]-N-methyl-1,3-propanediamine

Supplemental Hazard information (EU)

n.a.

SealBoss 15X

 Print date:
 May 10.2015
 Revision date: May 10, 2015
 EN

 Version:
 1
 Issue date: May 10, 2015
 Page 2 / 8

Labelling (67/548/EEC or 1999/45/EC)

×

Xi Irritant

Hazard statements

36/38 Irritating to eyes and skin.

43 May cause sensitization by skin contact.

Precautionary statements

24 Avoid contact with skin.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

37 Wear suitable gloves.

contains:

N-[2-[2-(dimethylamino) ethoxy] ethyl]-N-methyl-1,3- propanediamine

Special provisions concerning the labelling of certain mixtures

n.a.

2.3. Other hazards

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Product description / chemical characterization

Description: polyhydroxy alcohol - amine component for polyurethane foam resin

Hazardous ingredients:

Classification according to Regulation (EC) No. 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Chemical name classification:	Wt % Remark
216-940-1	01-2119976346-26-xxxx	
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	2,5 - 10
	Acute Tox. 4 H312 / Skin Corr. 1C H314 / Eye Dam. 1 H318	
470-720-1	01-000019735-62-xxxx	
189253-72-3	N-[2-[2-(dimethylamino) ethoxy] ethyl]-N-methyl-1,3-propanediamine	1 - 2,5
	Acute Tox. 4 H302 / Skin Corr. 1B H314 / Eye Dam. 1 H318 / Skin Sens.	
	1 H317	

Classification according to Directive 67/548/EEC or 1999/45/EC

EC No. CAS No. INDEX No.	REACH No. Chemical name classification:		
216-940-1 1704-62-7	01-2119976346-26-xxxx 2-[2-(dimethylamino)ethoxy]ethanol C; R34	2,5 - 10	
470-720-1 189253-72-3	01-0000019735-62-xxxx N-[2-[2-(dimethylamino) ethoxy] ethyl]-N-methyl-1,3- propanediamine C; R34 / R43 / Xn; R22	1 - 2,5	

Additional information

Full text of R-phrases: see section 16. Full text of H-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

SealBoss 15X

 Print date:
 May 10.2015
 Revision date: May 10, 2015
 EN

 Version:
 1
 Issue date: May 10, 2015
 Page 3 / 8

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Special protective equipment for firefighters:

Provide a conveniently located respiratory protective device.

Additional information

Cool closed containers that are near the source of the fire. Co-ordinate fire-fighting measures to the fire surroundings. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Use appropriate container to avoid environmental contamination.

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8.

Only use the material in places where open light, fire and other flammable sources can be kept away.

Always keep in containers that correspond to the material of the original container.

Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

SealBoss 15X
Print date: May 10.2015 Revision date:

May 10.2015 Revision date: May 10, 2015

Issue date: May 10, 2015 Page 4 / 8

ΕN

Hints on joint storage

Keep away from food, drink and animal feeding stuffs.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

n.a.

Version:

DNEL:

2-[2-(dimethylamino)ethoxy]ethanol

EC No. 216-940-1 / CAS No. 1704-62-7

DNEL long-term dermal (systemic), Workers: 2,33 mg/kg bw/day

DNEL long-term inhalative (local), Workers: 1,07 mg/m³

DNEL long-term inhalative (systemic), Workers: 0,48 mg/m³

PNEC:

2-[2-(dimethylamino)ethoxy]ethanol

EC No. 216-940-1 / CAS No. 1704-62-7

PNEC aquatic, freshwater: 0,1 mg/L PNEC

aquatic, marine water: 0,01 mg/L PNEC

aquatic, intermittent release: 1 mg/L

PNEC sediment, freshwater: 8,6957 x10^-2 mg/kg

PNEC sediment, marine water: 0,8696 x10^-2 mg/kg

PNEC, Soil: 2,8174 x10^-2 mg/kg

PNEC sewage treatment plant (STP): 100 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. When spraying, wear self-contained breathing apparatus.

Occupational exposure controls

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Hand protection

For prolonged or repeated handling the following glove material must be used: nitrile rubber or butyl rubber

Thickness of the glove material >0,4 mm; Breakthrough time (maximum wearing time) >480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear suitable protective clothing.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains.

See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state liquid

SealBoss 15X

 Print date:
 May 10.2015
 Revision date: May 10, 2015
 EN

 Version:
 1
 Issue date: May 10, 2015
 Page 5 / 8

ColourcolourlessOdourcharacteristic

Safety relevant basis data	Unit	Method	Remark
Flash point	> 101 ℃	DIN 53213	
Ignition temperature in °C	NB		
Lower explosion limit	NB		
Upper explosion limit	NB		
Vapour pressure at 20 °C	0,41 mbar		
Density at 20 °C	0,96 g/cm ³	DIN 51757	
Water solubility (g/L)	insoluble		
pH at 20 °C	-		
Viscosity at 23 °C	mPas		Observe technical
-			data sheet.
solvent content:			

solvent content:

Organic solvents: Wt %

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

102. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

2-[2-(dimethylamino)ethoxy]ethanol oral, LD50, Rat: 2150 mg/kg

dermal, LD50, Rabbit: > 1000 mg/kg

N-[2-[2-(dimethylamino) ethoxy] ethyl]-N-methyl-1,3-propanediamine

oral, LD50, Rat: 300 - 2000 mg/kg

Irritant and corrosive effects

2-[2-(dimethylamino)ethoxy]ethanol Skin

Sensitisation

Toxicological data are not available.

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

Toxicological data are not available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Toxicological data are not available.

Practical experience/human evidence

Other observations:

Overall Assessment on CMR properties

The ingredients in this preparation do not meet the criteria for classification as CMR category 1 or 2 according to 67/548/EEC.

There is no information available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

SECTION 12: Ecological information

overall evaluation

There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

12.1. Toxicity

N-[2-[2-(dimethylamino) ethoxy] ethyl]-N-methyl-1,3-propanediamine Fish toxicity, LC50, Cyprinus carpio (Common Carp): > 100 mg/L (96 h) Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 100 mg/L (48 h) Algae toxicity, ErC50, Selenastrum capricomutum: 64 mg/L (72 h)

Long-term Ecotoxicity

Toxicological data are not available.

122. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation:

Do not allow to enter into surface water or drains. Handle contaminated packages in the same way as the substance itself. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC:

070208 other still bottoms and reaction residues

packaging

Recommendation:

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

14.1. UN number

n.a.

142. UN proper shipping name

143. Transport hazard class(es)

n.a.

14.4. Packing group

n.a.

SealBoss 15X

May 10, 2015 Revision date: May 10, 2015 ΕN Print date: Version: Page 7 / 8 Issue date: May 10, 2015

14.5. Environmental hazards

Land transport (ADR/RID) n.a. Marine pollutant n.a.

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8.

Additional information

Land transport (ADR/RID)

tunnel restriction code

Sea transport (IMDG)

EmS-No. n.a.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation:

Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/L) ISO 11890-2: 0.000

National regulations:

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations:

Giscode: GISCODE PU 40

152. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

Relevant R-and H-phrases (Number and full text):

Acute Tox. 4 / H312 Acute toxicity (dermal) Harmful in contact with skin.

Skin Corr. 1C / H314 skin corrosion/irritation Causes severe skin burns and eye damage.

Eye Dam. 1 / H318 Serious eye damage/eye irritation Causes serious eye damage.

Acute Tox. 4 / H302 Acute toxicity (oral) Harmful if swallowed.

Skin Corr. 1B / H314 skin corrosion/irritation Causes severe skin burns and eye damage. Skin Sens. 1 / H317 May cause an allergic skin reaction.

respiratory or skin sensitisation

C; R34 Corrosive Causes burns.

R43 May cause sensitization by skin contact.

Xn: R22 Harmful Harmful if swallowed.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms





Danger

Hazard statements

Causes skin irritation. H315 H318 Causes serious eye damage. H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

SealBoss 15X

Print date:May 10.2015Revision date: May 10, 2015ENVersion:1Issue date: May 10, 2015Page 8 / 8

P302 + P352 IF ON SKIN: Wash with plenty of water/.?.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/.?.

Contains:

2-[2-(dimethylamino)ethoxy]ethanol

N-[2-[2-(dimethylamino) ethoxy] ethyl]-N-methyl-1,3-propanediamine

Supplemental Hazard information (EU)

n.a.

Recommended restrictions on use:

Training advice Data

sources: Additional

information

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

Disclaimer:

Limited Warranty Policy and Disclaimer for Products Supplied and/or Distributed by SealBoss Corp.: All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Material Safety Data Sheet prior to product use. SealBoss Corp. warrants supplied / distributed products to be free of manufacturing defects. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of the manufacturer which proves to be defective. There are no other warranties by SealBoss Corp. of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. SealBoss Corp. shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. SealBoss Corp. shall not be responsible for use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, UV damage, excessive temperature exposure, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and / or physical movement of the substrate or structural defect s are also excluded from the limited warranty. SealBoss Corp. reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations and statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller. SealBoss Corp. reserves the right to change the properties of products without notice.