Revision Date 04.16.2015 Revision: 1

1 Identification of the substance/mixture and the company/undertaking

1.1 Product identifier

Trade name: SealBoss 4500F - A-Side

1.2 Application of the substance / the mixture: Anchoring epoxy

1.3 Details of the supplier of the Safety Data Sheet Manufacturer/Supplier:

SealBoss Corporation 1669 E. Wilshire Ave. Santa Ana, CA 92705 Phone: 1-714-662-4445 Fax: 1-714-662-4446

1.4 Emergency telephone number:

ChemTel 1-800-255-3924 OR International: +01-813-248-0585

2 Hazards identification

2.1 GHS Classification of the substance or mixture

Skin Irritant 2; H315: Causes skin irritation. Eye Irritant 2; H319: Causes serious eye irritation.

Skin Sensitizer 1; H317: May cause and allergic skin reaction.

2.2 GHS Label elements

Hazard pictograms/symbols



Signal word: Warning

Hazard statements:

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H317: May cause and allergic skin reaction.

Precautionary statements:

P280: wear protective gloves / eye protection.

P273: Avoid release to the environment.

P264: Wash thoroughly after handling.

P261: Avoid breathing mist/vapours/spray.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do .Continue rinsing.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

Revision Date 04.16.2015 Revision: 1

P337+P313: If eye irritation persists: Get medical advice/attention.

Additional information:

Contains epoxy constituents. May produce an allergic reaction.

HMIS Rating:

Health: 2
Flammability: 1
Physical Hazard: 0

3 Composition/information on ingredients

3.2 Mixture

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:			
CAS: 25068-38-6	Reaction product: bisphenol - A- (epichlorohydrin) epoxy resin (number average molecular weight≤700)	>70%	
CAS: 29570-58-9	Dipentaerythritol Hexaacrylate	<10%	
CAS: 107-21-1	Ethylene glycol	<2%	

4 First aid measures

4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the

accident.

Take affected persons out into the fresh air.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Immediately rinse with water.

If skin irritation continues, consult a doctor.

After eye contact:

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not Induce vomiting: call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed:

Allergic reactions.

Nausea.

Coughing.

Gastric or intestinal disorders.

Irritant to skin and mucous membranes.

Irritant to eyes.

4.3 Indication of any immediate medical attention and special treatment needed:

Revision Date 04.16.2015 Revision: 1

Contains reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700). May produce an allergic reaction.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary edema.

Medical supervision for at least 48 hours.

5 Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Water haze or fog.

Foam.

Fire-extinguishing powder.

Carbon dioxide.

For safety reasons unsuitable extinguishing agents:

Water with full jet

Water spray

5.2 Special hazards arising from the substance or mixture:

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for the firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information:

Cool endangered receptacles with water fog or haze.

Eliminate all ignition sources if safe to do so.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers).

6.3 Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

7 Handling and storage

7.1 Precautions for safe handling:

Use only in well-ventilated areas.

Store in cool, dry place in tightly closed receptacles (60-80°F recommended).

7.2 Conditions for safe storage, including any incompatibilities:

Use only receptacles specifically permitted for this substance/product.

Revision Date 04.16.2015 Revision: 1

Avoid storage near extreme heat, ignition sources or open flame.

Further Information about storage conditions:

Keep container tightly sealed.

Store in an area with adequate ventilation.

8 Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs: No further relevant information available.

PNECs: No further relevant information available.

Additional information: The lists valid during the making were used as basis.

8.2 Engineering controls

Provide readily accessible eye wash stations and safety showers.

Provide ventilation adequate to ensure concentrations are minimized.

8.3 Personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

Not required under normal conditions of use.

Use suitable respiratory protective device in case of insufficient ventilation.

For spills, respiratory protection may be advisable.

Use respiratory protection when grinding or cutting material.

Hand protection:

Protective, impervious gloves. (Neoprene, PVC, Nitrile rubber)

The glove material has to be impermeable and resistant to the product / the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Eye protection:

Safety glasses with side shields.

Contact lenses should not be worn.

Skin and Body protection:

Protective work clothing.

Where potential exposure warrants, rubber or plastic boots and chemically resistant protective suit.

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties General Information Appearance

Revision Date 04.16.2015 Revision: 1

Form: Soft Paste Color: White Odor: Sweet

Odor threshold:

pH:

No data available

No data available

Melting point/range:No data availableBoiling point/range:>392 °F / >200 °C

Flash point: >302 °F / >150 °C
Evaporation rate: No data available
Flammability (solid, gaseous): Not applicable
Upper/lower flammability or explosive limit: Not applicable
Vapor pressure: No data available

Vapor density: No data available

Relative Density at 20 °C: 1.19 g/cm³

Solubility in / Miscibility with

Water:
Partition coefficient (n-octanol/water):
Auto/Self-ignition temperature:
Decomposition temperature:
Viscosity

Not miscible or difficult to mix.
No data available
No data available
No data available
150,000 – 300,000 cps

10 Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions:

Reacts with strong alkali. Exothermic polymerization.

Reacts with strong acids and oxidizing agents.

Reacts with catalysts.

10.4 Conditions to avoid:

Avoid contact with strong oxidizing agents, excessive heat or flames.

10.5 Incompatible materials:

Strong acids, bases and oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide.

11 Toxicological information

11.1 Information on likely routes of exposure:

Inhalation : May cause respiratory irritation

Ingestion: No data

Skin contact: May cause skin irritation
Eye contact: May cause eye irritation

11.2 Symptoms related to physical, chemical and toxicological characteristics: No available data

11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure:

(Data for primary hazardous component: Reaction product: bisphenol - A- (epichlorohydrin) epoxy resin)

Revision Date 04.16.2015 Revision: 1

Acute toxic:

Oral LD50 > 2,000 mg/kg (rat) Dermal LD50 > 2,000 mg/kg (rat)

Inhalation No data

Skin Corrosive/irritant:

Test material was slightly irritating to skin in key studies. For the skin, mean erythema and edema scores were 0.8 and 0.5 respectively.

Serious eye damage/eye irritation:

Test material was slightly irritating to the eye in key studies. The mean eye score

was 0.4

Respiratory sensitization: No data available

Skin sensitization:

In a local lymph node assay, the concentration that would cause a 3-fold increase in proliferation (EC-3) was calculated to be 5.7% which is consistent with moderate dermal sensitization potential.

11.4 Numerical measures of toxicity: No data available for mixture.

Additional toxicological information:

The product show the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant Danger through skin absorption.

Toxic and /or corrosive effects may be delayed up to 24 hours.

Inhalation of concentrated vapours as well as oral intake will lead to anesthesia-like conditions and headache.

dizziness, etc.

12 Ecological information

12.1 Toxicity

Aquatic toxicity:

(Data taken from SDS of primary hazardous component: Reaction product: bisphenol - A-(epichlorhydrin) epoxy resin)

Fish 96hr-LC50 = 3.6mg/L test mat. *Oncorhynchus mykiss*

(direct application, nominal) (OECD Guideline 203)

LC50 1.41 mg/L 96hr Oryzias latipes

Crustacea 48hr-EC50 = 2.8mg/L test mat *Daphnia magna*

(direct application, nominal, based on: mobility) (OECD Guideline 202)

EC50 1.7mg/L 48hr

Aquatic Plant 72hr-EC50 > 11 mg/L Scenedesmus capricornutum

water soluble fraction (meas. (arithm. mean)) based on: growth rate (EPA-660/3-75-009)

12.2 Persistence and degradability: No data available.

12.3 Bioaccumulative potential: No further relevant information available.

12.4 Mobility in soil: No further relevant information available.

12.5 Results of PBT and vPvB assessment:

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects: No further relevant information available

Revision Date 04.16.2015 Revision: 1

13 Disposal considerations

13.1 Waste treatment methods

Waste from residue/unused product:

This product should not be allowed to enter drains, water courses or the soil. Dispose of this material in a safe manner and in accordance with federal, state and local regulations

Contaminated packaging:

Disposal must be made in accordance with official federal, state and local regulations.

14 Transport information

DOT

UN number: Not Regulated

IATA

UN number: Not Regulated

IMDG

UN number: Not Regulated

TDG

UN number: Not Regulated

15 Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

United States (USA)

SARA

• ,	
Section 355 (extremely hazardous substances):
None of the ingredients is listed.	
Section 313 (Specific toxic chemical listings):	
Component(s) above 'de minimus' level: None	
TSCA (Toxic Substances Control Act):	
All the ingredients are listed.	

Proposition 65 (California):

Chemicals known to cause cancer: Silicon dioxide (dispersed in liquid medium; not in a respirable form)

Canada

Canadian Domestic Substances List (DSL):	
All ingredients are listed.	
Canadian Ingredient Disclosure list (limit 0.1%)	
None of the ingredients is listed.	
Canadian Ingredient Disclosure list (limit 1%)	
None of the ingredients is listed.	

Revision Date 04.16.2015 Revision: 1

15.2 Chemical Safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviation and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienist.

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substance

CAS: Chemical Abstracts Service (division of the American Chemical Society)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

Limited Warranty Policy and Disclaimer for Products Supplied and/or Distributed by SealBoss Corp.; All recommendations. statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Material Safety Data Sheet prior to product use. SealBoss Corp. warrants supplied / distributed products to be free of manufacturing defects. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of the manufacturer which proves to be defective. There are no other warranties by SealBoss Corp. of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. SealBoss Corp. shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. SealBoss Corp. shall not be responsible for use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, UV damage, excessive temperature exposure, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and / or physical movement of the substrate or structural defect s are also excluded from the limited warranty. SealBoss Corp. reserves the right to conduct performance test's on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations and statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller. SealBoss Corp. reserves the right to change the properties of products without notice.