



Sika Damp Proofing Slurry

Date of issue - 15/04/2002. SKTMO107

PRODUCT AND COMPANY IDENTIFICATION

Product Code SKTMO107

Product Name Sika Damp Proofing Slurry

Product Description 1-component polymer modified waterproofing cementitious coating.

Manufacturer/Supplier Sika Limited

Watchmead

Welwyn Garden City Hertfordshire. AL7 1BQ

tel. 01707 394444 Fax. 01707 329129

COMPOSITION/INFORMATION ON THE COMPONENTS

Preparation - Hazardous ingredients (Europe)

Component Concentration Classification Risk Phrases

1) Portland Cement 25.00% - 50.00% Xi R41,37/38

2) Pulverised fuel ash 1.00% - 2.50%

HAZARD IDENTIFICATION

Main Hazards Risk of serious damage to eyes.

Irritating to respiratory system and skin.

Health Effects - Inhalation Exposure to dust at high concentrations may have the following

effects:-

irritation of nose, throat and respiratory tract.

Respirable silica dusts if inhaled over a prolonged period could

constitute a health hazard.

FIRST AID MEASURES

Eye Contact Immediately flood the eye with plenty of water for at least 15 minutes,

holding the eye open.

Obtain medical attention urgently.

Skin Contact Wash skin thoroughly with soap and water.

Obtain medical attention if blistering occurs or redness persists. Contaminated clothing should be washed or dry-cleaned before re-use.

Ingestion Do not induce vomiting. Wash out mouth with water.

Inhalation Remove from exposure.

In cases of possible respiratory irritation or if feeling unwell in cases of

 $prolonged\ exposure, obtain\ medical\ attention.$

FIRE FIGHTING MEASURES

Extinguishing Media Not combustible.

Select extinguishing agent appropriate to other materials involved.

Special Hazards of Product None.

CM Version - 1 Page: 1/4



SAFETY DATA SHEET Sika Damp Proofing Slurry

Date of issue - 15/04/2002. SKTMO107

ACCIDENTAL RELEASE MEASURES

Personal Precautions Wear appropriate protective clothing.

Environmental Precautions and

Clean-up Methods

Spillages Avoid creating a dust.

Sweep up into suitable containers for recovery or disposal.

HANDLING AND STORAGE

Handling Avoid inhaling dust.

Exposure by inhalation or skin contact should be minimised by good

Try to prevent the material from entering drains or water courses.

Industrial Hygenie practices. Use in well ventilated area.

Storage Storage area should be: cool. dry.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits - GB

1) Portland Cement

UK EH40: OES 10mg/m3 8h TWA. Dust, total inhalable:
UK EH40: OES 4mg/m3 8h TWA. Dust, respirable:

UK EH40: OES 10mg/m3 8h TWA. Dust, total inhalable:
UK EH40: OES 10mg/m3 8h TWA. Dust, respirable:
UK EH40: OES 4mg/m3 8h TWA. Dust, respirable:

Engineering Control Measures Use of the basic principles of Industrial Hygiene will enable this

material to be used safely.

Every effort should be made to prevent airborne dusts arising during

mixing operations.

Respiratory Protection If limits are exceeded use an approved dust mask.

Hand Protection Wear suitable impervious gloves.

Eye Protection Dust tight goggles.

Body Protection Protective clothing should be worn which ensures that cementitious

materials do not come into contact with the skin. Particular care should be taken to ensure that wet mortar does not enter boots/footwear.

PHYSICAL AND CHEMICAL PROPERTIES

Physical StatePowder.ColorGrey/White.OdorNone.

pH Approx. 12 in water.Flash Point °C Not applicable.

Solubility - WaterPartially soluble. (< 1 %)</th>Density (kg/m3)Approx. 1700. (loose)

STABILITY AND REACTIVITY

Stability Stable under normal conditions.

Materials to avoid Strong mineral acids.

Hazardous Decomposition Products None known.

CM Version - 1 Page: 2/4



SAFETY DATA SHEET Sika Damp Proofing Slurry

Date of issue - 15/04/2002. SKTMO107

TOXICOLOGICAL INFORMATIO

Acute toxicity Low order of acute toxicity.

Eye irritation Cement is a severe eye irritant.

Gross exposures or untreated mild exposures can lead to chemical

burning and ulceration of the eye.

Skin irritation Cement and/or water/cement mixtures may cause irritant contact

dermatitis, and/or burns.

May cause allergic reactions to certain individuals.

ECOLOGICAL INFORMATION

Mobility The product is sparingly soluble in water.

Persistence/degradability Inorganic basis, therefore non biodegradable.

Ecotoxicity The product is expected to be non-hazardous to aquatic species.

DISPOSAL

Product Disposal As an inert material it may be disposed of via an approved solid waste

disposal facility.

Container Disposal Empty packaging may be disposed along with normal builders waste

via an authorised waste contractor.

TRANSPORT INFORMATION

ADR/RID Proper shipping name

IMDG: Proper shipping name

Not Regulated under IMDG

Not Regulated under IMDG

Not Regulated under ICAO

REGULATORY INFORMATION

Label Requirements Irritant

X

Risk Phrases Risk of serious damage to eyes.

Irritating to respiratory system and skin.

Safety Phrases Keep out of reach of children.

In case of contact with eyes, rinse immediately with plenty of water and

seek medical advice. Wear eye/face protection.

If swallowed, seek medical advice immediately and show this

container or label.

OTHER INFORMATION

First Issue Date 15.04.2002

Revisions Highlighted Future revisions will incorporate such information as is required but

which is not available at this time.

Uses and Restrictions Customers are urged to ensure that the product is entirely suitable for

their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of

the product is undertaken.

CM Version - 1 Page: 3/4



SAFETY DATA SHEET Sika Damp Proofing Slurry

Date of issue - 15/04/2002.

SKTMO107

UK Legislation

Health and Safety at Work etc Act, 1974, and relevant Statutory

Provisions.

Chemicals (Hazard Information and Packaging) Regulations, 2002. SI 1999/437: The Control of Substances Hazardous to Health

Regulations

SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.

UK Guidance Publications

SI No. 972/1996: The Special Waste Regulations 1996 General Approved Code of Practice to COSHH Regulations, HSE. EH40, Occupational Exposure Limits, HSE. Revised Annually. EH44, Dust in the Workplace: General Principles of Protection, HSE. EH26, Occupational Skin Diseases: Health and Safety Precautions,

HSE.

CONIAC Health Hazard Information Sheet No.26 (Cement)

Footnote

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the

Technical Data Sheet prior to use.