



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor®-10 Pronto

1.2 Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

Product use : Flooring system.

1.3 Details of the supplier of the safety data sheet

Company : Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire AL7 1BQ
United Kingdom

Telephone : +44 (0)1707 394444

1.4 Emergency telephone number

Emergency telephone number : +44 (0)1707 363899 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

Classification (67/548/EEC, 1999/45/EC)

Highly flammable	R11: Highly flammable.
Harmful	R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
Sensitising	R43: May cause sensitisation by skin contact.
Irritant	R37/38: Irritating to respiratory system and skin.



R33: Danger of cumulative effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.

Precautionary statements : **Prevention:**
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 Keep container tightly closed.
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Response:
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P312 Call a POISON CENTER or doctor/ physician if you feel unwell.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

- 201-297-1 methyl methacrylate

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).
 This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
methyl methacrylate 80-62-6	F; R11 Xi; R37/38	Flam. Liq.2; H225 STOT SE3; H335	>= 50 - <= 100



201-297-1	R43	Skin Irrit.2; H315 Skin Sens.1; H317	
N,N-dimethyl-p-toluidine 99-97-8 202-805-4	T; R23/24/25 R33 R52/53	Acute Tox.3; H301 Acute Tox.2; H330 Acute Tox.3; H311 STOT RE2; H373 Aquatic Chronic3; H412	>= 1 - < 2,5

For the full text of the R-phrases mentioned in this Section, see Section 16.
 For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Cough
Respiratory disorder
Allergic reactions
Erythema
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects
sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.



SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO₂), Dry chemical

Unsuitable extinguishing media : Water, High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.



SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding of the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products

- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against electrostatic discharges.

- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters *	Basis *
methyl methacrylate	80-62-6	TWA	50 ppm 208 mg/m3	GB EH40
		STEL	100 ppm 416 mg/m3	GB EH40



		TWA	50 ppm	2009/161/EU
		STEL	100 ppm	2009/161/EU

8.2 Exposure controls

Personal protective equipment

- Eye protection : Safety glasses with side-shields
Eye wash bottle with pure water

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

 Suitable for short time use or protection against splashes:
 Butyl rubber/nitrile rubber gloves (0,4 mm),
 Contaminated gloves should be removed.
 Suitable for permanent exposure:
 Viton gloves (0.4 mm),
 breakthrough time >30 min.

- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

- Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
 organic vapor filter (Type A)
 A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
 Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

- General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.



SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: colourless
Odour	: unpleasant
Odour Threshold	: No data available
Flash point	: ca. 10 °C
Autoignition temperature	: ca. 430 °C
Lower explosion limit	: 2 %(V)
Upper explosion limit	: 12,5 %(V)
Flammability (solid, gas)	: No data available
Oxidizing properties	: No data available
Auto-ignition temperature	: No data available
pH	: Note: not determined
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: ca. 100 °C
Vapour pressure	: ca.38,7 hPa at 20 °C
Density	: ca.1 g/cm ³ at 20 °C
Water solubility	: Note: insoluble
Partition coefficient: n-octanol/water	: No data available
Viscosity, dynamic	: ca.200 mPa.s at 20 °C
Viscosity, kinematic	: > 20,5 mm ² /s at 40 °C
Relative vapour density	: No data available
Evaporation rate	: No data available
Self-heating	: , no



9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

N,N-dimethyl-p-toluidine :

Acute oral toxicity : Acute toxicity estimate : 100 mg/kg
Method: Converted acute toxicity point estimate

Acute dermal toxicity : Acute toxicity estimate : 300 mg/kg
Method: Converted acute toxicity point estimate

Skin corrosion/irritation

Product

Causes skin irritation.

Serious eye damage/eye irritation

Product

No data available



Respiratory or skin sensitisation

Product

May cause an allergic skin reaction.

Germ cell mutagenicity

Product

Mutagenicity : No data available

Carcinogenicity

Product

Carcinogenicity : No data available

Reproductive Toxicity/Fertility

Reproductive toxicity : No data available

No data available

Reproductive Toxicity/Development/Teratogenicity

Teratogenicity : No data available

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil



No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- European Waste Catalogue : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances
- Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

ADR

- 14.1 UN number** : 1247
14.2 Description of the goods : METHYL METHACRYLATE MONOMER, STABILIZED
14.3 Class : 3
14.4 Packing group : II
Classification Code : F1
Labels : 3
Tunnel restriction code : (D/E)
14.5 Environmentally hazardous : no

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikafloor®-10 Pronto



Revision Date 26.08.2014

Print Date 26.08.2014

IATA

14.1 UN number : 1247
14.2 Description of the goods : Methyl methacrylate monomer, stabilized
14.3 Class : 3
14.4 Packing group : II
Labels : 3
14.5 Environmentally hazardous : no

IMDG

14.1 UN number : 1247
14.2 Description of the goods : METHYL METHACRYLATE, MONOMER, STABILIZED
14.3 Class : 3
14.4 Packing group : II
Labels : 3
EmS Number 1 : F-E
EmS Number 2 : S-D
14.5 Marine pollutant : no

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Labelling according to EC Directives (1999/45/EC)

Hazard pictograms :



Highly flammable



Harmful

R-phrases : R11 Highly flammable.
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
R33 Danger of cumulative effects.
R37/38 Irritating to respiratory system and skin.
R43 May cause sensitisation by skin contact.

S-phrases : S36/37 Wear suitable protective clothing and gloves.

Hazardous components which must be listed on the label:

- 201-297-1 methyl methacrylate
- 202-805-4 N,N-dimethyl-p-toluidine



Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : not applicable

REACH Information: All substances contained in our Products are
- preregistered or registered by our upstream suppliers, and/or
- preregistered or registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

VOC-CH (VOCV) : no VOC duties

VOC-EU (solvent) : not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002
Control of Substances Hazardous to Health Regulations 2002
The Management of Health and Safety at Work Regulations 1999
Health and Safety at Work Act 1974
Environmental Protection Act 1990 & Subsidiary Regulations

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of R-Phrases

R11 Highly flammable.
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
R33 Danger of cumulative effects.
R37/38 Irritating to respiratory system and skin.
R43 May cause sensitisation by skin contact.
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Full text of H-Statements

H225 Highly flammable liquid and vapour.
H301 Toxic if swallowed.
H311 Toxic in contact with skin.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor®-10 Pronto



Revision Date 26.08.2014

Print Date 26.08.2014

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Chronic	Chronic aquatic toxicity
Flam. Liq.	Flammable liquids
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any any use and processing.

|| Changes as compared to previous version !